



**RHINO-CRYL  
6000**

## **RHINO-CRYL 6000 Exterior Hi-Sheen Satin (6401 to 6404)**

**RHINO-CRYL 6000 Exterior Hi-Sheen Satin:** A high quality, extremely durable, chalk-resistant, 100% acrylic finish for a wide variety of exterior surfaces. It produces a high hiding, breathing type finish with outstanding adhesion and resistance to blistering, weathering and moisture. Mildewcide provides for added protection from mildew in high humidity climates. Benefits include rich, hi-satin finish that repels dirt and moisture, excellent adhesion, fast drying, low odor and easy clean-up.

**Recommended Substrates:** Properly Prepared Exterior Drywall and Siding, Plaster, Concrete, Wood, Previously Painted or Primed Metal Applications.

**Application:** Stir product thoroughly with a circular, lifting motion ensuring even mixing throughout. Apply by brush, roller or airless spray. Product may be thinned with clean water, but is packaged ready to use. Best results are more likely obtained by using quality tools. Do not apply directly over chalky surfaces or bleeding stains. Apply when temperature is between 38°F and 95°F. \*Drying time will vary depending on temperature, air circulation and humidity. Low temperature application is limited to white and medium colors. The surface and air temperature should remain above 38°F. If painting in cold conditions, the temperature must not fall below freezing for at least 8 hours after application.

**Product Type:** 100% Acrylic Resin  
**Volume Solids:** 35.40 ± 1.0%  
**Sheen:** 35% to 40% at 60°  
**VOC:** max of 100 g/L

**Dry Time:** to touch = 1 hour; recoat = 4 hours; drying time will vary depending on temperature, air circulation and humidity.

**Coverage:** 375 sq/ft per gallon (coverage will vary depending on application, surface texture, porosity and color) at 1.5 MIL dry film.

**Thinner:** Clean water.

**Clean Up:** Warm, soapy water.

**Disposal:** Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Do not pour down a drain or storm sewer.

The surface to be painted must be clean and free of dirt, chalk, mildew, wax, grease, rust or loose, flaking paint and other contaminants. Patch and sand smooth cracks and nail holes. Sand hard glossy surfaces to dull gloss and roughen the surface. Sand or wire brush to remove loose and flaking paint. Spot prime all patching work.

**Warning:** Use only with adequate ventilation. Ensure fresh air during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Contains Ethylene Glycol & Crystalline Silica.

In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention immediately; for skin, wash thoroughly with soap and water. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced get medical attention immediately. If swallowed, get medical attention immediately.

If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

Obtain and read the MSDS prior to using this product. **KEEP OUT OF REACH OF CHILDREN.**