



**SPEC-PRO®  
1000**

**Series**

**Spec-Pro 1000 Eggshell (SPC1201)**

**Spec-Pro 1000 Eggshell:** A latex eggshell that provides a smooth finish on interior walls and ceilings. Easy to apply, safe waterborne formula to be used in commercial and multi-family markets.

**Recommended Substrates:** Concrete, Concrete/Masonry Block, Ferrous Metal, Gypsum Wallboard-Drywall, Plaster, Wood

**Application:** Stir thoroughly before using and occasionally during use. Apply with a high quality brush, roller, paint pad, or by airless spray equipment. Apply a second coat where necessary. For airless spray, pressure 2000 psi and tip 0.015" - 0.021". For brush and roll application, use polyester or nylon with 3/16" - 3/8" nap roller cover. Thinning is usually not required. If necessary, thin with up to 1/4 pint of water per U.S. gallon of paint. Apply only when surface and air temperatures are between 50 and 90 degrees Fahrenheit. Covers approximately 400 sq. ft./gal. on smooth, nonporous surfaces.

**Product Type:** Vinyl Acrylic Latex  
**Volume Solids:** 30% ± 2%  
**Weight Solids:** 46% ± 2%  
**Weight Per Gallon:** 10.8 lbs. ± 0.2 lbs.  
**Flash Point:** Over 200 degrees Fahrenheit  
**Sheen:** Eggshell: 2 to 6 (60 degree Gloss Meter)  
**Wet Film Thickness:** 4.0 mils  
**Dry Film Thickness:** 1.2 mils  
**VOC:** 43 g/L (0.4 lbs/gal)

**Dry Time:** to touch = 1 hour; recoat = 4 hours; full cure = 30 days. Dry time @ 77 degrees Fahrenheit; 50% relative humidity.

**Thinner:** Clean water.

**Clean Up:** Warm, soapy water.

**Disposal:** Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Do not pour down a drain or storm sewer.

Surfaces to be coated must be dry, clean, sound and free from all contamination including loose and peeling paint, dirt, grease, oil, wax, concrete curing agents and bond breakers, chalk, efflorescence, mildew, rust, product fines and dust. Remove loose paint, chalk and efflorescence by wire brushing, scraping, sanding and/or pressure washing. Putty all nail holes and caulk all cracks and open seams. Sand all glossy, rough and patched surfaces. Feather back all rough edges to sound surface by sanding. Apply primer over soluble stains before coating to avoid bleeding. Prime all bare and porous substrates with an appropriate primer.

**Warning:** Use only with adequate ventilation. Ensure fresh air during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. If you scrape, sand or remove old paint, you may release lead dust or fumes. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention immediately; for skin, wash thoroughly with soap and water. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced get medical attention immediately. If swallowed, get medical attention immediately.

If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

Obtain and read the MSDS prior to using this product. **KEEP OUT OF REACH OF CHILDREN.**