



**SPEC-PRO  
2000**  
Series

### **SPEC-PRO 2000 Interior Flat (2101 to 2103)**

**SPEC-PRO 2000 Flat:** An interior product with a flat, latex finish that provides good hide and works well for residential, multi-family and commercial applications. Outstanding uniformity with superior scrub resistance. Excellent touch up.

**Recommended Substrates:** Drywall, Plaster, Concrete, Wood, Previously painted or primed metal

**Application:** Stir product thoroughly with a circular, lifting motion ensuring even mixing throughout. Apply by brush, roller or airless spray. Product may be thinned with clean water, but is packaged ready to use. Best results are more likely obtained by using quality tools. Do not apply directly over chalky surfaces or bleeding stains. Apply when temperature is between 50 and 95 degrees Fahrenheit. Avoid frost, fog and damp conditions.

**Product Type:** Vinyl Acrylic Emulsion

**Volume Solids:** 33 ± 1.0%

**Sheen:** < 3% at 60°

**VOC:** max of 100 g/L

**Dry Time:** to touch = 1 hour; recoat = 4 hours; drying time will vary depending on temperature, air circulation and humidity.

**Coverage:** 300-400 sq/ft per gallon (coverage will vary depending on application, surface texture, porosity and color).

**Thinner:** Clean water.

**Clean Up:** Warm, soapy water.

**Disposal:** Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Do not pour down a drain or storm sewer.

The surface to be painted must be clean and free of dirt, chalk, mildew, wax, grease, rust or loose, flaking paint. Dirt and chalk should be removed by scrubbing with warm soapy water and thoroughly rinsed with clean water. Mildew must be removed by scrubbing with a solution of one part household bleach and three parts water. Rinse well with clean water and allow it to dry thoroughly before painting. Wax should be removed with a commercial wax stripper or by solvent cleaning. Grease should be cleaned by using an appropriate emulsifier. Rust must be removed by hand sanding or by conscientious power tool cleaning. Remove loose paint, feather sand rough edges, dull glossy surfaces by light sanding. Remove sanding dust before paint application. Any exposed substrate should be spot primed with an appropriate primer.

**Warning:** Use only with adequate ventilation. Ensure fresh air during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Contains Ethylene Glycol & Crystalline Silica.

In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention immediately; for skin, wash thoroughly with soap and water. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced get medical attention immediately. If swallowed, get medical attention immediately.

If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

Obtain and read the MSDS prior to using this product. **KEEP OUT OF REACH OF CHILDREN.**