



Technical Bulletin

SHARPSHOOTER™ **SPEC-PRO®** SILICONIZED ACRYLIC LATEX CAULK

Manufactured for:
Spectrum Paint
15247 E. Skelly Dr.
Tulsa, Oklahoma 74116
Phone: 918-398-2188
www.spectrumpaint.com

- 40 year performance guarantee
- Minimal shrinkage
- Easy to tool
- Paintable, water clean-up
- Interior/exterior

Product Description:

SPECTRUM PAINT SHARPSHOOTER™ is multi-purpose acrylic latex caulk with silicone additives designed exclusively for the professional paint contractor. It offers excellent paintability. Silicone additives ensure excellent adhesion and flexibility as well as minimal shrinkage. This formulation will not crack, has no after flow and is easy to tool in all climates. Interior/exterior use. Cured sealant is mildew resistant. It exceeds ASTM C834 Specification. 40 year performance guarantee.

Performance Characteristics:

- Exceeds the ASTM specification requirements of C834.
- 40 year performance guarantee.
- Can be painted with latex and oil-based paints.

Suggested Applications:

Windows & Doors	Siding & Trim
Drywall	Glass
Pipes & vents (non-heated)	Countertops
Brick & Masonry	Molding & Baseboards
Most common building materials	

Suggested Substrates

Wood	Painted Surfaces
Drywall	Glass
Brick	Metal
Plaster	

Surface Preparation:

- Surface must be clean, dry & free of old caulk, dirt, dust & grease.
- Apply in temperatures above 40°F. Do not apply when rain or freezing temperatures are forecasted before full cure can occur.
- Do not use below waterline, for filling butt joints, surface defects or tuck-pointing.
- Joint size should not exceed 1/2" wide x 1/2" deep. If joint depth exceeds 1/2", use backer rod material.

Application:

- Cut nozzle at a 45° angle to desired bead size.
- Load cartridge into caulking gun.
- Fill gap with caulk, pushing caulk ahead of nozzle.
- Smooth bead.
- Clean up excess uncured caulk with damp sponge before it skins over. Cured caulk must be cut or scraped away.
- Allow to dry 2 hours (longer in cool/humid conditions) before painting with latex or oil-based paints.
- Reseal cartridge for storage & reuse.



SHARPSHOOTER™

SILICONIZED ACRYLIC LATEX CAULK

SPEC-PRO®

Physical & Chemical Characteristics:

Tooling Time:	10-15 Minutes
Tack-Free Time:	30 Minutes
Dynamic Joint Movement:	± 12%
Life Expectancy:	40 years
Paintability:	Yes
Odor:	Very Mild
Consistency:	Smooth and Creamy
Vehicle:	Silicone Acrylic Polymer
Volatile:	Water
Flash Point:	None
Pigment:	Calcium Carbonate
Density:	1.64 ± 0.01
Solids:	82% ± 1.0% by weight
Weight per Gallon:	13.7 ± 0.10 lbs./gal.
Temperature Service Range:	-20°F to 180°F
Temperature Application Range:	40°F to 100°F
Freeze Thaw Stability:	Passes 5 Cycles
Shelf Life:	12 months
Packaging:	Standard – 10.1 fl. oz. Cartridge
Coverage:	56 linear ft. per cartridge at a 3/16" bead size. Three average-size doors or four average-size windows.

Clean Up and Storage:

- Before curing, remove excess material with a damp cloth.
- After product has cured, excess material must be cut or scraped away.
- Store in a cool, dry place away from extreme heat or cold.

Safety:

- See product label or Safety Data Sheet for safety information.
- You can request an SDS sheet by calling 1-866-437-5863 or visit www.spectrumpaint.com/techmsds.

Packaging: 10.1 fl. oz. (299 ml)

Color: White

Item: 18890

UPC Number: 7079818890