



SPEC-PRO®

Spec-Pro® Buildermax®
Interior PVA Primer
33000

GENERAL DESCRIPTION

This fine-quality, interior PVA latex primer/sealer is high hiding and sandable. Use on properly prepared, previously painted surfaces or use to prime interior, properly prepared, bare wood, masonry, and unpainted wallboard.

RECOMMENDED SUBSTRATES

Gypsum Wallboard-Drywall
Oriented Strand Board
Particle Board
Wood

CONFORMANCE STANDARDS

VOC compliant in all regulated areas

PRODUCT INFORMATION

DR53360 White

PACKAGING

Quart (946 mL)
1-Gallon (3.78 L)
5-Gallon (18.9 L)

Not all products are available in all sizes.

LIMITATIONS OF USE

FOR INTERIOR USE ONLY. Apply when air, product and surface temperatures are between 50°F (10°C) and 90°F (32°C).

Not recommended for use on floors.

PROTECT FROM FREEZING.

FEATURES / BENEFITS

Features

Good adhesion
Good sealing properties
Good holdout
Easy application
Easy soap and water cleanup

Benefits

Improves durability of finish
Provides a uniform finish
Promotes even sheen in topcoats
Can be used by any type applicator
Waterborne formula

PRODUCT DATA

PRODUCT TYPE: Vinyl Acrylic Latex
SHEEN: Flat: 2 to 6 @ 60°
VOLUME SOLIDS*: 27% +/- 2%
WEIGHT SOLIDS*: 42% +/- 2%
WEIGHT/GALLON*: 10.5 lbs. (4.8 kg) +/- 0.2 lbs. (91 g)
VOC: <100 g/L (0.8 lbs./gal.)

COVERAGE: Approximately 400 sq. ft. (37 sq. meters) per U.S. Gallon (3.78L) on smooth, nonporous surfaces.

Wet Film Thickness: 4 mils
Wet Microns: 102
Dry Film Thickness: 1.1 mils
Dry Microns: 28

Coverage figures do not include loss due to surface irregularities and porosity or material loss due to application method or mixing. Some colors, drastic color changes, or porous substrates may require more than one coat to achieve a uniform finish.

DRYING TIME: Dry time @ 77°F (25°C); 50% relative humidity.
To Touch: 1 hour
To Recoat: 4 hours

Drying times listed may vary depending on temperature, humidity, film build, color, and air movement.

CLEANUP: Clean tools with warm, soapy water.

DISPOSAL: Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.

FLASH POINT: Over 200°F (93°C)

PRECAUTIONS

WARNING! HARMFUL IF INHALED. HARMFUL IF SWALLOWED. Do not breathe vapor or mist. Do not swallow. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling. Provide fresh air ventilation during and after application and drying. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Use personal protective equipment as required.

Note: These warnings encompass the product series. Prior to use, read and follow product-specific SDS and label information.

FIRST AID: If swallowed, rinse mouth with water (only if the person is conscious). Call physician immediately. Do not induce vomiting unless directed to do so by medical personnel. If in eyes, rinse with water for 15 minutes. Check for and remove any contact lenses. If on skin, rinse well with water. Wash with soap and water. Get medical attention if irritation develops. If inhaled, remove to fresh air. Call physician immediately. Contains isothiazolinones. May cause allergic reaction. Keep out of the reach of children. For workplace use, an SDS is available from your retailer or by calling (412) 492-5555. EMERGENCY SPILL INFORMATION: (412) 434-4515 (U.S.)