



# SPEC-ONE Ultra-Seal Precatalyzed Sealer

## DESCRIPTION

SPEC-ONE Ultra Seal Precat Sealer is a high quality precatalyzed lacquer sealer designed to be used in conjunction with Spectrum Paint's 680 VOC precatalyzed topcoats. Ultra Seal provides rapid cure schedules and exceptional sanding properties. Ultra Seal meets all of the pertinent government regulations regarding emissions and exceeds the performance parameters outlined by KCMA and ASTM. For wood substrates only. For interior use only.

PRODUCT NUMBERS / SHEENS	COATING PROPERTIES	PREPARATION INSTRUCTIONS
<div data-bbox="178 525 446 609" style="font-size: 2em; text-align: center;">15010</div> <div data-bbox="159 714 462 745" style="background-color: black; color: white; padding: 2px;"><b>PRODUCT ADVANTAGES</b></div> <ul style="list-style-type: none"> <li>Virtually HAP's Free</li> <li>AIM Compliant</li> <li>User Friendly</li> <li>Improved Flow and Leveling</li> <li>Faster Dry Time</li> <li>Water Clear</li> <li>No Critical Recoat Time</li> <li>Non Photo Chemically Reactive</li> <li>Phthalate Free</li> <li>Exceeds KCMA and ASTM Performance Requirements, When Applied to Specification</li> </ul> <p><i>Note: These numbers represent actual control values on a smooth, sanded substrate. Spray techniques, texture, and sealing as well as film thickness may give different results on actual work, but they may be used for comparison. To the best of our knowledge, the above technical data is true and accurate at the date of issuance but is subject to change without prior notice.</i></p>	<p><b>Viscosity:</b> 21 #2 Zahn  <b>Weight Solids:</b> 22%  <b>Volume Solids:</b> 16%  <b>Weight/Gallon:</b> 7.49 lbs./gal  <b>Coverage:</b> 256 sq. ft. per gallon at one mil dry film thickness.</p> <p><b>VOC (coating):</b> 5.63 lbs./gl. or 674 g/l  <b>VOC (material):</b> 4.52 lbs./gl. or 542 g/l  <b>VOC Ratio:</b> 2.72 lbs. VOC/lbs. solids  <b>HAPS Ratio:</b> 0.08 lbs. HAPS/lbs. solids</p> <p><b>Dry Times:</b>  <b>Air Dry:</b> at 78°F, relative humidity 50%            To touch: 7 minutes            To Handle: 9 minutes            To sand/recoat: 15 minutes  <b>Force Dry:</b>            Flash: 8-10 minutes            Bake: 15 min @ 110° F            Cool down: 10 min            Stack immediately after cool down            Relative humidity will affect the speed of drying. Ideal conditions are 75°F or warmer at 50% humidity or less. Dry time will be faster at higher temperatures and lower humidity and equally slower at colder temperatures and higher humidity.</p> <p><b>Dry Film Thickness:</b> Maximum DFT for this system should not exceed 4 mils dry.</p> <p><b>Pot Life:</b> 12 months</p> <p><b>Shelf Life:</b> 12 months @77° F if unopened and stored in a cool dry area. Always rotate stock.</p> <p><b>Storage:</b> Keep away from heat or sparks.</p>	<p><b>Catalyzation:</b> This product comes pre-catalyzed. Do NOT add catalyst.</p> <p><b>Reduction:</b>  <b>Thinning:</b> If needed due to conditions in your facility use HAPs Free Reducer at levels not to exceed 5% by volume*</p> <p><b>Retarder:</b> If a slower dry time is desired, use Haps Free Retarder at levels not to exceed 3% by volume*</p> <p>*Thinning this material may result in increasing the VOC levels of this product. Refer to your local regulations before thinning.</p> <p><b>Approved Companion Products</b>  <b>15910 Clear Gloss</b>  <b>15510 Clear Semi Gloss</b>  <b>15310 Clear Satin</b>  <b>15210 Clear 20 Sheen</b>  <b>15110 Clear Flat</b></p>

Updated July 5, 2016

The following supersedes any provision contained in the forms, letters and papers of your company. This product is designed and intended for professional application only. All products should be thoroughly tested under application conditions prior to use. The information contained herein is believed to be reliable. **HOWEVER, SPECTRUM PAINT MAKES NO WARRANTY CONCERNING THIS PRODUCT, WHETHER EXPRESS OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** UNDER NO CIRCUMSTANCES SHALL SPECTRUM PAINT BE LIABLE FOR SPECIAL, INCIDENTAL, CONSEQUENTIAL, OR ANY OTHER DAMAGES FROM ALLEGED NEGLIGENCE, BREACH OF WARRANTY, STRICT LIABILITY, OR ANY OTHER LEGAL THEORY, ARISING OUT OF THE USE OR HANDLING OF THIS PRODUCT. THE SOLE REMEDY OF THE BUYER AND THE SOLE LIABILITY OF SPECTRUM PAINT FOR ANY CLAIMS SHALL BE LIMITED TO THE BUYER'S PURCHASE PRICE OF THE PRODUCT WHICH IS THE SUBJECT OF THE CLAIM OR THE AMOUNT ACTUALLY PAID FOR SUCH PRODUCT, WHICHEVER IS LESS. TECHNICAL ADVICE FURNISHED BY SPECTRUM PAINT SHALL NOT CONSTITUTE AN EXPRESS WARRANTY, WHICH IS EXPRESSLY DISCLAIMED. ALL TECHNICAL ADVICE GIVEN IS ACCEPTED AT THE RISK OF THE BUYER. **CAUTION: DANGER! FLAMMABLE! VAPORS MAY CAUSE FLASH FIRE. VAPOR HARMFUL. HARMFUL OR FATAL IF SWALLOWED. INJURIOUS TO EYES. KEEP OUT OF THE REACH OF CHILDREN! BEFORE using this product it is essential that the "Safety Data Sheet" describing the product as well as the "Product Label" be reviewed. If your company does not have such information or has any questions, contact Spectrum Paint.**

## PRODUCT DATA SHEET SPEC-ONE 15010 CONTINUED



### Substrate preparation:

**New wood:** Remove any dirt, grease, glue or other contaminants. Moisture content of wood should be 7-9%.

Sand to 150-180 grit. Proper sanding of wood is absolutely critical to achieve the best color development and adhesion of the coating to the substrate.

**Old wood:** Strip old finishes completely and remove all contaminants from the surface. Make sure the surface is dry, sand as required. Finish as new work.



### Mixing Instructions:

Mix material thoroughly before and during use. Material may be mixed by hand or mechanical agitation at moderate speed.



### Application:

If staining, apply the Spectrum Paint approved stain of your choosing and let dry per the instructions on the PDS for that particular stain. Using conventional, HVLP, airless, or air assisted equipment, apply this sealer at 3-4 wet mils per coat. Let dry a minimum of 15 minutes. Sand with 280-320 grit no-fill sandpaper and remove sanding dust with clean compressed air, or tack rag. This sealer must be sanded before applying a topcoat.

Typically we recommend a coating system comprised of one coat of 15010 applied at 3-4 mils wet film build and 1-2 coats of topcoat applied at 3-4 mils wet film build. Approved topcoats for use with this sealer is our 15x10 series clear Precatalyzed Lacquers. Please refer to the PDS for dry film limitations for the complete system.



### Recommended Tip Sizes:

Conventional Air	1.2-1.8mm
HVLP	1.3-1.5mm
Airless	10-15 thousandths
Air Assisted Airless-	11-15 thousandths



### Precautions:

These products are intended for Professional use only. Do not proceed if you are planning on mixing with other finishing systems or other manufacturer's products. Spectrum Paint will not be held liable for finish failures due to the improper use of our products or deviation from our finishing recommendations

### Equipment:

All equipment used with this product must have plastic, stainless steel, or Teflon fluid passages and wetted parts

### Containers:

We supply this material in a lined container. All containers used in conjunction with storage and/or application of this product must be stainless steel, plastic, or otherwise acid resistant.

### Clean up:

Use lacquer thinner to clean up all equipment. Dispose of in accordance with Federal, State, and Local regulation regarding pollution.

**Care and cleaning of this finish:** Use a mild dishwashing liquid and a damp cloth to remove food, grease, and other residue. Wipe dry. Do not use cleaners that contain ammonia, bleach, or abrasives as this may damage the finish.