



SECTION 1: CHEMICAL AND MANUFACTURER IDENTIFICATION

Product Name: SPECTRUM ADMIRAL PRECAT CLEAR SEALER Product Code: 17010

Spectrum Paint
15247 E Skelly Dr.
Tulsa, OK 74116
918-398-2188
E-mail: info@spectrumpaint.com

24 Hour Emergency: INFOTRAC: 1-800-535-5053

Outside U.S. and Canada: Infotrac: 352-323-3500

INFOTRAC Customer ID: 99624

NOTE: INFOTRAC and National Response Center emergency numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals

Not recommended for:

Because many of the conditions are within the user's knowledge and control, it is essential that the user evaluate and determine whether the product is suitable and appropriate for a particular use and intended application, and complies with all local applicable laws, regulations, standards, and guidance.

SECTION 2: HAZARD(S) IDENTIFICATION

Prepared according to Global Harmonized System (GHS) Standards

GHS Classification Scale

1=Severe Hazard; 4=Slight Hazard

GHS Ratings:

Flammable liquid	2	Flash point < 23°C and initial boiling point > 35°C (95°F)
Skin corrosive	2	Reversible adverse effects in dermal tissue, Draize score: >= 2.3 < 4.0 or persistent inflammation
Eye corrosive	2A	Eye irritant: Subcategory 2A, Reversible in 21 days
Organ toxin single exposure	3	Transient target organ effects- Narcotic effects- Respiratory tract irritation
Organ toxin repeated exposure	2	Presumed to be harmful to human health- Animal studies with significant toxic effects relevant to humans at generally moderate exposure (guidance)- Human evidence in exceptional cases

GHS Hazards

H225	Highly flammable liquid and vapour
H315	Causes skin irritation
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H373	May cause damage to organs through prolonged or repeated exposure

GHS Precautions

P210	Keep away from heat, sparks, open flames and hot surfaces. No smoking!
P233	Keep container tightly closed
P240	Ground / bond container and receiving equipment
P241	Use explosion-proof electrical, ventilating, lighting equipment
P242	Use only non-sparking tools
P243	Take precautionary measures against static discharge
P260	Do not breathe dust/fume/gas/mist/vapours/spray
P261	Avoid breathing dust/fume/gas/mist/vapours/spray
P264	Wash thoroughly after handling
P271	Use only outdoors or in a well-ventilated area
P280	Wear protective gloves, protective clothing, eye protection, face protection
P312	Call a POISON CENTER or doctor/physician if you feel unwell
P314	Get Medical advice/attention if you feel unwell
P321	Specific treatment (see first aid section on this label/SDS)
P362	Take off contaminated clothing and wash before reuse
P302+P352	IF ON SKIN: Wash with soap and water
P303+P361+P353	IF ON SKIN (or hair): Remove / Take off all contaminated clothing immediately. Rinse skin thoroughly with water / shower
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
P305+P351+P338	IF IN EYES: Rinse continuously with cool water for at least 15 minutes. Remove contact lenses if present and easy to do. Continue rinsing.
P332+P313	If skin irritation occurs: Get medical advice/attention
P337+P313	If eye irritation persists get medical advice / attention
P370+P378	In case of fire: Use dry chemical / CO2 / foam for extinction
P405	Store locked up
P403+P233	Store in a well ventilated area. Keep container tightly closed.
P403+P235	Store in a well ventilated area. Keep cool
P501	Dispose of contents / container to an approved waste disposal facility

Signal Word: Danger



SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS number	Weight Concentration %
Isopropyl alcohol	67-63-0	20.00% - 30.00%
n-Butyl acetate	123-86-4	20.00% - 30.00%
Acetone	67-64-1	5.00% - 10.00%
Nitrocellulose	9004-70-0	5.00% - 10.00%
Xylenes (o-, m-, p- isomers)	1330-20-7	5.00% - 10.00%
Ethyl acetate	141-78-6	5.00% - 10.00%
Naphtha, petroleum, hydrotreated light	64742-49-0	1.00% - 5.00%
2-Pentanone, 4-methyl-	108-10-1	1.00% - 5.00%
Isobutyl alcohol	78-83-1	1.00% - 5.00%
Ethylbenzene	100-41-4	0.10% - 1.00%
Stoddard solvent	8052-41-3	0.10% - 1.00%

SECTION 4: FIRST AID MEASURES

Inhalation: Move affected person to fresh air. If breathing has stopped, administer CPR. If the person vomits, clean the airway and turn their head to the side to prevent choking. If the person is unconscious but breathing, place them stably on their left side in the recovery position. Never give anything by mouth to an unconscious person. Seek immediate medical attention.

Eyes: Flush eyes gently with clean water for at least 15 minutes. If irritation persists, seek immediate medical attention.

Skin: Remove any contaminated clothing using appropriate gloves. Rinse skin thoroughly for 15 minutes in a shower or with a hose. Seek immediate medical attention.

Ingestion: Rinse mouth with water to remove any residual chemical. If the person vomits, clean their airway and turn their head to the side to prevent choking. DO NOT induce vomiting and DO NOT give them anything to drink unless directed to do so by a physician. If the person is unconscious but breathing, place them stably on their left side in recovery position. Never give anything by mouth to an unconscious person. Seek immediate medical attention.

Additional Notes to Physician - Treat symptomatically. No specific antidote available

SECTION 5: FIREFIGHTING MEASURES

Flash Point: -20 C (-4 F)

LEL: 1.0%

UEL: N/A

Suitable Extinguishing Media:

Foam

Carbon Dioxide (CO₂)

Dry Chemical

Specific Hazards During Firefighting: Prevent firefighting run-off from entering drains or sewers.

Byproducts of Combustion: Fires involving this product may release oxides of carbon and nitrogen, reactive hydrocarbons, and irritating vapors.

Unusual Fire and Explosion Hazards: Any closed container may rupture when exposed to extreme heat. Use a water spray to cool sealed containers. Solvent vapors are heavier than air and can travel along the ground.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Spill / Leak Clean-Up Procedures:

Immediately turn off or isolate any source of ignition (pilot lights, electrical equipment, flames, heaters, etc.). Evacuate area and ventilate. Personnel wearing proper protective equipment should contain spill immediately with inert materials (sand, earth, chemical spill pads of cotton) by forming dikes. Dikes should be placed to contain spill in a manner that will prevent material from entering sewers and waterways. Large spills, once contained, may be picked up using explosion proof, non-sparking vacuum pumps, shovels, or buckets, and disposed of in suitable containers. If a large spill occurs notify the appropriate authorities.

In case of road spill or accident contact INFOTRAC (1-800-535-5053).

CAUTION: If spilled material is cleaned up using a regulated solvent, the resulting waste mixture will also be regulated.

Do not empty into drains. All disposal must comply with federal, state, and local regulations. The material, if spilled or discarded, may be a regulated waste. Refer to state and local regulations. Department of Transportation (DOT) regulations may apply for transporting this material when spilled. See Section 14.

SECTION 7: HANDLING AND STORAGE

Handling Precautions:

Open containers carefully and in a well ventilated area, and use appropriate respiratory protection. Wash hands thoroughly after handling. Keep containers closed when not in use. Do not transfer to unmarked containers. Empty containers contain product residue which may exhibit hazardous properties therefore, do not pressurize, cut, glaze, weld or use for any other purpose. Return drums to reclamation center for proper cleaning and reuse.

Storage Requirements:

Store in a cool, dry, well ventilated area. Keep containers tightly closed and store away from heat, sparks, open flame or oxidizing materials. Extended storage at excessive temperatures may produce odorous and toxic fumes from product decomposition.

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Isopropyl alcohol 67-63-0	400 ppm TWA; 980 mg/m3 TWA	400 ppm STEL 200 ppm TWA	NIOSH: 400 ppm TWA; 980 mg/m3 TWA 500 ppm STEL; 1225 mg/m3 STEL
n-Butyl acetate 123-86-4	150 ppm TWA; 710 mg/m3 TWA	200 ppm STEL 150 ppm TWA	NIOSH: 150 ppm TWA; 710 mg/m3 TWA 200 ppm STEL; 950 mg/m3 STEL
Acetone 67-64-1	1000 ppm TWA; 2400 mg/m3 TWA	750 ppm STEL 500 ppm TWA	NIOSH: 250 ppm TWA; 590 mg/m3 TWA
Nitrocellulose 9004-70-0	Not Established	Not Established	Not Established
Xylenes (o-, m-, p- isomers) 1330-20-7	100 ppm TWA; 435 mg/m3 TWA	150 ppm STEL 100 ppm TWA	Not Established
Ethyl acetate 141-78-6	400 ppm TWA; 1400 mg/m3 TWA	400 ppm TWA	NIOSH: 400 ppm TWA; 1400 mg/m3 TWA
Naphtha, petroleum, hydrotreated light 64742-49-0	Not Established	Not Established	Not Established
2-Pentanone, 4-methyl- 108-10-1	100 ppm TWA; 410 mg/m3 TWA	75 ppm STEL 20 ppm TWA	NIOSH: 50 ppm TWA; 205 mg/m3 TWA 75 ppm STEL; 300 mg/m3 STEL
Isobutyl alcohol 78-83-1	100 ppm TWA; 300 mg/m3 TWA	50 ppm TWA	NIOSH: 50 ppm TWA; 150 mg/m3 TWA

Ethylbenzene 100-41-4	100 ppm TWA; 435 mg/m3 TWA	20 ppm TWA	NIOSH: 100 ppm TWA; 435 mg/m3 TWA 125 ppm STEL; 545 mg/m3 STEL
Stoddard solvent 8052-41-3	500 ppm TWA; 2900 mg/m3 TWA	100 ppm TWA	NIOSH: 350 mg/m3 TWA 1800 mg/m3 Ceiling (15 min)

Engineering Controls: Avoid creating dust or mist. Local exhaust ventilation, process enclosures, or other engineering controls are required when handling or using this product to avoid over exposure. Use explosion-proof ventilation equipment. Do not use in closed or confined spaces. Keep all levels below exposure limits. Perform regular monitoring to ensure exposure limits are not exceeded.

Personal Protective Equipment (PPE):

Respiratory Protection - Do not breathe vapors. When concentrations exceed the established limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA) until vapors are exhausted. Observe OSHA standard 29 CFR 1910.134 and ANSI Z88.2 requirements whenever workplace conditions require a respirators use.

Hand Protection - Wear appropriate protective gloves and clothing to prevent skin exposure. Gloves must be inspected prior to use. Use proper glove removal technique (without touching gloves outer surface) to avoid skin contact with this product.

Eye Protection - Use safety eyewear with splash guards or side shields. Use additional eye protection such as chemical safety goggles when the possibility for eye contact from splashing, spraying liquid, or airborne material exists.

Skin Protection - Avoid contact with this product. Wear appropriate protective gloves and clothing to prevent skin exposure. Use proper glove and clothing removal techniques to avoid skin contact with this product. When handling large quantities, eye wash stations and deluge showers should be available.

Hygiene Measures:

General - When using do not eat or drink. Wash hands with soap and water before breaks and at the end of each workday.

Contaminated Equipment - Avoid contact with contaminated clothing and protective gear/equipment. Wash before reuse.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

This mixture typically exhibits the following properties under normal circumstances:

Appearance Liquid Dispersion Physical State Liquid Lbs VOC/Gallon Less Water 5.58 g VOC/L Less Water 668.80	Odor Organic Solvent Specific Gravity (SG) 0.913 Flash point: -20°C, -4°F Boiling range: 56 - 141°C
--	--

SECTION 10: STABILITY AND REACTIVITY

Product Stability (under normal conditions):

STABLE

Incompatible Materials: Strong acids, strong bases, oxidizing agents

Avoid contact with Acids and Oxidizers

Hazardous Decomposition Products: Carbon Dioxide (CO₂), Carbon Monoxide (CO), Oxides of Nitrogen (NO_x), dense black smoke

None

Hazardous polymerization will not occur.

SECTION 11: TOXICOLOGICAL INFORMATION**Mixture Toxicity**

Inhalation Toxicity LC50: 121mg/L

Note - Toxicological studies have not been performed on this mixture. The toxicological data listed is compiled using data from the components of the mixture. Refer to Section 2 of this SDS for GHS classification of acute and chronic effects of exposure.**Principle Routes of Exposure:**

Inhalation Skin Contact Eye Contact Ingestion

May cause damage to the following organs:

Eyes Kidneys Liver Lungs Central Nervous System Skin Respiratory System

Carcinogenicity: The following chemicals comprise 0.1% or more of this mixture and are listed and/or classified as carcinogens or potential carcinogens by NTP, IARC, OSHA (mandatory listing) or ACGIH (optional listing):

<u>CAS Number</u>	<u>Description</u>	<u>% Weight</u>	<u>Carcinogen Rating</u>
100-41-4	Ethylbenzene	0.1% - 1.0%	IARC: Possible human carcinogen OSHA: listed
108-10-1	2-Pentanone, 4-methyl-	1% - 5%	IARC: Possible human carcinogen OSHA: listed
64742-49-0	Naphtha, petroleum, hydrotreated light	1% - 5%	EU REACH: Present (P)
8052-41-3	Stoddard solvent	0.1% - 1.0%	EU REACH: Present (P)

SECTION 12: ECOLOGICAL INFORMATION**Bioaccumulative Potential:** No data available**Mobility in Soil:** No data available**Persistence and Degradability:** No data available**Component Ecotoxicity**

Isopropyl alcohol

96 Hr LC50 Pimephales promelas: 9640 mg/L [flow-through]; 96 Hr LC50 Pimephales promelas: 11130 mg/L [static]; 96 Hr LC50 Lepomis macrochirus: >1400000 µg/L
 48 Hr EC50 Daphnia magna: 13299 mg/L
 96 Hr EC50 Desmodesmus subspicatus: >1000 mg/L; 72 Hr EC50 Desmodesmus subspicatus: >1000 mg/L

n-Butyl acetate

96 Hr LC50 Lepomis macrochirus: 100 mg/L [static]; 96 Hr LC50 Pimephales promelas: 17 - 19 mg/L [flow-through]
 72 Hr EC50 Desmodesmus subspicatus: 674.7 mg/L

Acetone	96 Hr LC50 Oncorhynchus mykiss: 4.74 - 6.33 mL/L; 96 Hr LC50 Pimephales promelas: 6210 - 8120 mg/L [static]; 96 Hr LC50 Lepomis macrochirus: 8300 mg/L 48 Hr EC50 Daphnia magna: 10294 - 17704 mg/L [Static]; 48 Hr EC50 Daphnia magna: 12600 - 12700 mg/L
Xylenes (o-, m-, p- isomers)	96 Hr LC50 Pimephales promelas: 13.4 mg/L [flow-through]; 96 Hr LC50 Oncorhynchus mykiss: 2.661 - 4.093 mg/L [static]; 96 Hr LC50 Oncorhynchus mykiss: 13.5 - 17.3 mg/L; 96 Hr LC50 Lepomis macrochirus: 13.1 - 16.5 mg/L [flow-through]; 96 Hr LC50 Lepomis macrochirus: 19 mg/L; 96 Hr LC50 Lepomis macrochirus: 7.711 - 9.591 mg/L [static]; 96 Hr LC50 Pimephales promelas: 23.53 - 29.97 mg/L [static]; 96 Hr LC50 Cyprinus carpio: 780 mg/L [semi-static]; 96 Hr LC50 Cyprinus carpio: >780 mg/L; 96 Hr LC50 Poecilia reticulata: 30.26 - 40.75 mg/L [static] 48 Hr EC50 water flea: 3.82 mg/L; 48 Hr LC50 Gammarus lacustris: 0.6 mg/L
Ethyl acetate	96 Hr LC50 Pimephales promelas: 220 - 250 mg/L [flow-through]; 96 Hr LC50 Oncorhynchus mykiss: 484 mg/L [flow-through]; 96 Hr LC50 Oncorhynchus mykiss: 352 - 500 mg/L [semi-static] 48 Hr EC50 Daphnia magna: 560 mg/L [Static]
2-Pentanone, 4-methyl-	96 Hr LC50 Pimephales promelas: 496 - 514 mg/L [flow-through] 48 Hr EC50 Daphnia magna: 170 mg/L 96 Hr EC50 Pseudokirchneriella subcapitata: 400 mg/L
Isobutyl alcohol	96 Hr LC50 Pimephales promelas: 1370 - 1670 mg/L [flow-through]; 96 Hr LC50 Pimephales promelas: 375 mg/L [static] (fry); 96 Hr LC50 Lepomis macrochirus: 1480 - 1730 mg/L [flow-through]; 96 Hr LC50 Oncorhynchus mykiss: 1120 - 1520 mg/L [flow-through] 48 Hr EC50 Daphnia magna: 1300 mg/L; 48 Hr EC50 Daphnia magna: 1070 - 1933 mg/L [Static]
Ethylbenzene	96 Hr LC50 Oncorhynchus mykiss: 11.0 - 18.0 mg/L [static]; 96 Hr LC50 Oncorhynchus mykiss: 4.2 mg/L [semi-static]; 96 Hr LC50 Pimephales promelas: 7.55 - 11 mg/L [flow-through]; 96 Hr LC50 Lepomis macrochirus: 32 mg/L [static]; 96 Hr LC50 Pimephales promelas: 9.1 - 15.6 mg/L [static]; 96 Hr LC50 Poecilia reticulata: 9.6 mg/L [static] 48 Hr EC50 Daphnia magna: 1.8 - 2.4 mg/L 72 Hr EC50 Pseudokirchneriella subcapitata: 4.6 mg/L; 96 Hr EC50 Pseudokirchneriella subcapitata: >438 mg/L; 72 Hr EC50 Pseudokirchneriella subcapitata: 2.6 - 11.3 mg/L [static]; 96 Hr EC50 Pseudokirchneriella subcapitata: 1.7 - 7.6 mg/L [static]

SECTION 13: DISPOSAL CONSIDERATIONS

Do not discharge product into sewer system. Dispose of in a licensed facility. Waste management should be in full compliance with federal, state, and local laws.

The transportation, storage, treatment and disposal of RCRA waste material must be conducted in compliance with 40 CFR 262, 263, 264, 268 and 270. Chemical additions, processing, or otherwise altering this material may make the waste management information presented in this SDS incomplete, inaccurate or otherwise inappropriate.

SECTION 14: TRANSPORT INFORMATION

This material is classified for transport as follows:

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>Hazard Class</u>
U.S. DOT	Paint	1263	II	3

SECTION 15: REGULATORY INFORMATION

Additional regulatory listings where applicable

State of California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986) WARNING! This product contains the following substance(s) which are listed by the State of California as carcinogenic, or a reproductive toxin:

- 108-10-1 2-Pentanone, 4-methyl- Carcinogen
- 100-41-4 Ethylbenzene Carcinogen
- 50-00-0 Formaldehyde Carcinogen

Clean Air Act, Section 112, Hazardous Air Pollutants (HAPs) (see 40 CFR 61) This product contains the following substance(s) which are listed as hazardous air pollutants (HAPs) per the Clean Air Act:

- 1330-20-7 Xylenes (o-, m-, p- isomers)
- 108-10-1 2-Pentanone, 4-methyl-
- 100-41-4 Ethylbenzene

Massachusetts Right To Know This product contains the following toxic or hazardous substance(s) which appear on the Massachusetts Substance List:

- 67-63-0 Isopropyl alcohol
- 123-86-4 n-Butyl acetate
- 67-64-1 Acetone
- 9004-70-0 Nitrocellulose
- 1330-20-7 Xylenes (o-, m-, p- isomers)
- 141-78-6 Ethyl acetate
- 108-10-1 2-Pentanone, 4-methyl-
- 78-83-1 Isobutyl alcohol
- 100-41-4 Ethylbenzene
- 8052-41-3 Stoddard solvent

New Jersey Worker and Community Right to Know Hazardous Substance List The following substance(s) appear on the New Jersey Right to Know Hazardous Substance List:

- 67-63-0 Isopropyl alcohol
- 123-86-4 n-Butyl acetate
- 67-64-1 Acetone
- 9004-70-0 Nitrocellulose
- 1330-20-7 Xylenes (o-, m-, p- isomers)
- 141-78-6 Ethyl acetate
- 108-10-1 2-Pentanone, 4-methyl-
- 78-83-1 Isobutyl alcohol
- 100-41-4 Ethylbenzene
- 8052-41-3 Stoddard solvent

Commonwealth of Pennsylvania Worker and Community Right To Know Act This product contains the following substance(s) which appear on the Pennsylvania Hazardous Substance List:

- 67-63-0 Isopropyl alcohol
- 123-86-4 n-Butyl acetate
- 67-64-1 Acetone
- 9004-70-0 Nitrocellulose
- 1330-20-7 Xylenes (o-, m-, p- isomers)
- 141-78-6 Ethyl acetate
- 108-10-1 2-Pentanone, 4-methyl-
- 78-83-1 Isobutyl alcohol
- 100-41-4 Ethylbenzene
- 8052-41-3 Stoddard solvent

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) This product contains a chemical or chemicals which are subject to the reporting requirements of the Act, and Title 40, of the Code of Federal Regulations, part 372:

67-63-0 Isopropyl alcohol
1330-20-7 Xylenes (o-, m-, p- isomers)
108-10-1 2-Pentanone, 4-methyl-
100-41-4 Ethylbenzene

Canadian DSL All substances in this product except those listed below are listed or exempt from reporting:

67-63-0 Isopropyl alcohol
123-86-4 n-Butyl acetate
67-64-1 Acetone
9004-70-0 Nitrocellulose
1330-20-7 Xylenes (o-, m-, p- isomers)
141-78-6 Ethyl acetate
64742-49-0 Naphtha, petroleum, hydrotreated light
6422-86-2 1,4-Benzenedicarboxylic acid, bis(2-ethylhexyl) ester
108-10-1 2-Pentanone, 4-methyl-
68002-18-6 Urea, polymer with formaldehyde, isobutylated
78-83-1 Isobutyl alcohol
100-41-4 Ethylbenzene
8052-41-3 Stoddard solvent

Country	Regulation	All Components Listed
Canada	Canadian NDSL	No
Australian	Australian Inventory of Chemical Substances	No
Japan	Existing and New Chemical Substances	No
China	Inventory of Existing Chemical Substances Produced	No
New Zealand	Inventory of Chemicals	No
Philippines	Philippine Inventory of Chemicals and Chemical	No
	Reach PBT/vPvB	No

TSCA Substance Control Act (TSCA) All substances except those listed below appear in the Toxic Substances Control Act, Chemical Substance Inventory:

- None

SECTION 16: OTHER INFORMATION

Disclaimer: The Volatile Organic Compound (VOC) content reported herein, if any, is based on a material VOC calculation. Several methods are used for the calculation of VOC content, and the standards and requirements regarding VOC content vary by location or jurisdiction.

This document has been prepared using data from sources considered to be technically reliable and is believed to be correct as of the date hereof. It does not constitute a warranty, expressed or implied, as to the accuracy of the information contained herein. Actual conditions of use and handling are beyond the seller's control. User is responsible to evaluate all available information when using product for any particular use, and to comply with all federal, state, provincial, and local laws and regulations.

Manufacturer:

A.P. Nonweiler Co., Inc.

3321 County Road A

PO Box 1007

Oshkosh, WI 54903-1007

(920) 231-0850

E-mail: sds@apnonweiler.com

Revision Notes:

Reviewer Revision

Date Prepared: 4/19/2023