



# **Technical Data Sheet**

## **Product Name**

# **Spectrum Admiral Pre-Catalyzed Clear Sealer**

Product Code: 17010

# **Product Description**

A clear precatalyzed sanding sealer for use under Spectrum Admiral clear lacquers. For Professional use only. Wood Substrates only.

#### **Features**

- Dries to a tough, easy to sand finish.
- Is ready to spray as supplied
- Provides a good foundation for Spectrum clear lacquers.

# **Technical Data**

Viscosity: 35-45 seconds #2 Signature Zahn

Sheen Level: N/A

Density: 7.55-7.75 lbs./gallon

% Solids by weight: 27.74-29.74%

Dry to sand & recoat: 30-45 minutes

### **Surface Prep**

Surface area must be clean and dust free with a moisture content not to exceed more than 8% prior to application. Proper sanding, and keeping the application area free of dust, are instrumental to achieve the best results.

### **Application Guidelines**

All products should be stirred before use and continually agitated while in use for best results. This product can be applied by airless or air assisted spray. All surfaces must be clean and dry. Sand bare wood with 150 grit sandpaper. Apply 3-4 wet mils per coat. Do not exceed 5 mils DFT. After applying, allow to dry for 30-45 minutes, sand with 220-320 grit sandpaper, and wipe away all sanding dust before applying a finish coat. For interior use only.

#### Disclaimer

Spectrum Paint Co. certifies the above product meets the agreed upon performance specifications. Spectrum Paint Co. is not responsible for the misuse and subsequent product failure. No warranty is expressed or implied in such instances. All products utilized in conjunction with 17010 need to be tested in advance to ensure compatibility. User assumes all risk with such endeavors. Consult the SDS for specific hazards. For technical support, please contact your local Spectrum Paint account manager or store.