



# DOMINION

## EXTERIOR FLAT ACRYLIC

### SP691

#### Features

- 100% Acrylic
- Crack and peel resistant
- Extremely durable
- 20 Year Warranty

#### General Description

Dominion Exterior Paint Flat is a high quality, extremely durable, chalk-resistant, 100% acrylic finish for exterior surfaces. Produces a high hiding, breathing type finish with outstanding adhesion and resistance to blistering, weathering and moisture.

#### Recommended For

For exterior wood, masonry, hardboard and metal in commercial, institutional and residential applications. Use on exterior siding, foundations, fascia, shutters or retaining walls.

#### Limitations

- Do not apply when air and surface temperatures are below 40 °F (4.4 °C).
- Not for interior use

#### Product Information

<b>Colors:</b> White Tint Base (01)	<b>Technical Data<sup>◇</sup></b>	<b>White Tint Base</b>
<b>Tint Bases:</b> Mid-Tone Base (02) Neutral Base (04)	<hr/>	
<b>Technical Assistance:</b> 866-437-5863  <b>Spectrum Paint Company, Inc.</b> 15427 E. Skelly Drive Tulsa, OK 741161	<hr/>	
<hr/>		Vehicle Type <span style="float: right;">100% Acrylic</span>
<hr/>		Pigment Type <span style="float: right;">Titanium Dioxide</span>
<hr/>		Volume Solids <span style="float: right;">38 ± 1.0%</span>
<hr/>		Coverage per Gallon at Recommended Film Thickness <span style="float: right;">350 – 450 Sq. Ft.</span>
<hr/>		Recommended Film Thickness <span style="float: right;">3.7 – 4.5 mils</span>
<hr/>		Recommended Film Thickness <span style="float: right;">1.4 – 1.7 mils</span>
<hr/>		– Wet <span style="float: right;">3.7 – 4.5 mils</span>
<hr/>		– Dry <span style="float: right;">1.4 – 1.7 mils</span>
Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure color uniformity and minimize the disposal of excess paint.		
<hr/>		Dry Time @ 77 °F <span style="float: right;">1 Hour</span>
<hr/>		(25 °C) @ 50% RH <span style="float: right;">4 Hours*</span>
<hr/>		– Tack Free <span style="float: right;">1 Hour</span>
<hr/>		– To Recoat <span style="float: right;">4 Hours*</span>
*When temperatures are below 50°F, allow 24 hours before recoating. Do not apply if snow, rain, frost, fog or damp conditions are expected within 24 hours after application.		
<hr/>		Dries By <span style="float: right;">Evaporation, Coalescence</span>
<hr/>		Viscosity <span style="float: right;">100 ± 4 KU</span>
<hr/>		Flash Point <span style="float: right;">N/A</span>
<hr/>		Gloss / Sheen <span style="float: right;">Flat (1 – 4 @ 85°)</span>
<hr/>		Surface Temperature at Application <span style="float: right;">40 °F</span>
<hr/>		– Min. <span style="float: right;">100 °F</span>
<hr/>		– Max. <span style="float: right;">100 °F</span>
<hr/>		Thin With <span style="float: right;">Clean Water</span>
<hr/>		Clean Up Thinner <span style="float: right;">Warm Soapy Water</span>
<hr/>		Weight Per Gallon <span style="float: right;">11.3 lbs.</span>
<hr/>		Storage Temperature <span style="float: right;">40 °F</span>
<hr/>		– Min. <span style="float: right;">90 °F</span>
<hr/>		– Max. <span style="float: right;">90 °F</span>
<hr/>		
<hr/>		
<hr/>		
<hr/>		
<hr/>		
<hr/>		
<hr/>		
<hr/>		
<hr/>		
<hr/>		
<hr/>		
<hr/>		
<hr/>		
<hr/>		
<hr/>		
<hr/>		
<hr/>		
<hr/>		
<hr/>		
<hr/>		

## Dominion Exterior Flat Acrylic SP691

### Surface Preparation

All surfaces should be clean, dry, free from dirt, dust, grease, oil, wax and other contaminants. Mold and mildew must be removed. Dull any glossy surfaces. Pressure wash and/or scrape surfaces to remove any cracked, peeling or blistering paint. Do not apply over chalky paint. Spot prime bare areas or surfaces in poor condition with recommended primer.

**Caution:** Refer to the detergent solution's data and material safety data sheet for instructions on its proper use and handling. For metal surfaces, remove all active rust. Wipe down with paint thinner to remove surface oils.

All new masonry substrates must be allowed to cure for 30 days before priming or painting.

### Priming

**Wood (Non-bleeding):** Apply 1-2 coats of Dominion

**Wood (Bleeding):** Prime redwood, cedar and other bleeding woods with a stain blocking primer

**Galvanized and Aluminum:** Apply an acrylic metal primer

**Ferrous Metal:** Apply a rust-inhibitive metal primer.

**Masonry:** Apply 1-2 coats of Dominion

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Informational Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**WARRANTY:** Spectrum Paint warrants that at the time of sale this product conforms with applicable Spectrum Paint specifications and is free of manufacturing defects. Spectrum Paint's sole liability for products proven defective, and Purchaser's sole remedy, if any, shall be replacement of the product or refund of the purchase price paid, at the sole option of Spectrum Paint. This warranty is not transferable.

**TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAW, SPECTRUM PAINT MAKES NO OTHER WARRANTIES, GUARANTEES, OR REPRESENTATIONS OF ANY KIND, EITHER EXPRESS OR IMPLIED, OR BY USAGE OF TRADE, AND HEREBY EXPRESSLY EXCLUDES AND DISCLAIMS ALL IMPLIED WARRANTIES, OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. IN NO EVENT SHALL SPECTRUM BE LIABLE FOR PUNITIVE, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES OF ANY KIND.**

Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation may not apply to you. This Limited Warranty gives you specific legal rights and you may have other rights which vary from State to State.

### Application

Stir product with a circular, lifting motion before you begin to paint. Dominion may be applied by brush, spray or roller, at a rate of application not to exceed 450 square feet per gallon. Surface texture and porosity will affect actual yield. For best brush application results, use a quality synthetic filament brush. For roller application, use a 3/8" or 1/2" nap cover for smooth surfaces, a 3/4" nap cover for semi-rough surfaces and a 1" or 1 1/2" nap cover for rough surfaces. For spray application, thin with clean water, up to 20% reduction if necessary. Do not apply when surface or air temperatures are below 40 °F. Do not apply to hot surfaces or in direct sunlight. Do not apply if rain is threatening.

### Clean Up

Clean up with warm, soapy water followed by a clean water rinse.

USE COMPLETELY OR DISPOSE OF PROPERLY. Dry empty containers may be recycled in a can recycling program. **Local disposal requirements vary; consult your sanitation department or state-designated environmental agency on disposal options.**

### Environmental Health & Safety Information

#### WARNING!

**Possible birth defect hazard.** Contains, **Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester**, which may cause birth defects based on animal data.

**Use only with adequate ventilation.** Do not breathe vapors, spray mist or sanding dust. Ensure fresh air entry during application and drying. Avoid contact with eyes and prolonged or repeated contact with skin. Avoid exposure to dust and spray mist by wearing a NIOSH approved respirator during application, sanding and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling.



**WARNING:** Cancer and Reproductive Harm—  
[www.P65warnings.ca.gov](http://www.P65warnings.ca.gov)

**FIRST AID:** In case of eye contact, flush immediately with plenty of water for at least 15 minutes; for skin, wash thoroughly with soap and water. If symptoms persist, seek medical attention. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

**IN CASE OF SPILL** – Absorb with inert material and dispose of as specified under "Clean up".

**KEEP OUT OF REACH OF CHILDREN  
PROTECT FROM FREEZING**

**Refer to Safety Data Sheet for  
additional health and safety information.**