



DOMINION

EXTERIOR SATIN ACRYLIC SP693

Features

- 100% Acrylic
- Crack and peel resistant
- Extremely durable
- 20 Year Warranty

General Description

Dominion Exterior Paint Satin is a high quality, extremely durable, chalk-resistant, 100% acrylic finish for exterior surfaces. Produces a high hiding, breathing type finish with outstanding adhesion and resistance to blistering, weathering and moisture.

Recommended For

For exterior wood, masonry, hardboard and metal in commercial, institutional and residential applications. Use on exterior siding, foundations, fascia, shutters or retaining walls.

Limitations

- Do not apply when air and surface temperatures are below 40 °F (4.4 °C).
- Not for interior use

Product Information

<p>Colors: White Tint Base (01)</p>	<p>Technical Data \diamond</p> <table border="1"> <tr> <td>Vehicle Type</td> <td>100% Acrylic</td> </tr> <tr> <td>Pigment Type</td> <td>Titanium Dioxide</td> </tr> <tr> <td>Volume Solids</td> <td>39 \pm 1.0%</td> </tr> <tr> <td>Coverage per Gallon at Recommended Film Thickness</td> <td>350 – 450 Sq. Ft.</td> </tr> <tr> <td>Recommended Film Thickness</td> <td>– Wet 3.6 – 4.6 mils – Dry 1.4 – 1.8 mils</td> </tr> <tr> <td colspan="2">Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure color uniformity and minimize the disposal of excess paint.</td> </tr> <tr> <td>Dry Time @ 77 °F (25 °C) @ 50% RH</td> <td>– Tack Free 1 Hour – To Recoat 4 Hours*</td> </tr> <tr> <td colspan="2">*When temperatures are below 50°F, allow 24 hours before recoating. Do not apply if snow, rain, frost, fog or damp conditions are expected within 24 hours after application.</td> </tr> <tr> <td>Dries By</td> <td>Evaporation, Coalescence</td> </tr> <tr> <td>Viscosity</td> <td>101 \pm 4 KU</td> </tr> <tr> <td>Flash Point</td> <td>N/A</td> </tr> <tr> <td>Gloss / Sheen</td> <td>Satin (20 – 30 @ 60°)</td> </tr> <tr> <td>Surface Temperature at Application</td> <td>– Min. 40 °F – Max. 100 °F</td> </tr> <tr> <td>Thin With</td> <td>Clean Water</td> </tr> <tr> <td>Clean Up Thinner</td> <td>Warm Soapy Water</td> </tr> <tr> <td>Weight Per Gallon</td> <td>11.3 lbs.</td> </tr> <tr> <td>Storage Temperature</td> <td>– Min. 40 °F – Max. 90 °F</td> </tr> </table>	Vehicle Type	100% Acrylic	Pigment Type	Titanium Dioxide	Volume Solids	39 \pm 1.0%	Coverage per Gallon at Recommended Film Thickness	350 – 450 Sq. Ft.	Recommended Film Thickness	– Wet 3.6 – 4.6 mils – Dry 1.4 – 1.8 mils	Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure color uniformity and minimize the disposal of excess paint.		Dry Time @ 77 °F (25 °C) @ 50% RH	– Tack Free 1 Hour – To Recoat 4 Hours*	*When temperatures are below 50°F, allow 24 hours before recoating. Do not apply if snow, rain, frost, fog or damp conditions are expected within 24 hours after application.		Dries By	Evaporation, Coalescence	Viscosity	101 \pm 4 KU	Flash Point	N/A	Gloss / Sheen	Satin (20 – 30 @ 60°)	Surface Temperature at Application	– Min. 40 °F – Max. 100 °F	Thin With	Clean Water	Clean Up Thinner	Warm Soapy Water	Weight Per Gallon	11.3 lbs.	Storage Temperature	– Min. 40 °F – Max. 90 °F
Vehicle Type	100% Acrylic																																		
Pigment Type	Titanium Dioxide																																		
Volume Solids	39 \pm 1.0%																																		
Coverage per Gallon at Recommended Film Thickness	350 – 450 Sq. Ft.																																		
Recommended Film Thickness	– Wet 3.6 – 4.6 mils – Dry 1.4 – 1.8 mils																																		
Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure color uniformity and minimize the disposal of excess paint.																																			
Dry Time @ 77 °F (25 °C) @ 50% RH	– Tack Free 1 Hour – To Recoat 4 Hours*																																		
*When temperatures are below 50°F, allow 24 hours before recoating. Do not apply if snow, rain, frost, fog or damp conditions are expected within 24 hours after application.																																			
Dries By	Evaporation, Coalescence																																		
Viscosity	101 \pm 4 KU																																		
Flash Point	N/A																																		
Gloss / Sheen	Satin (20 – 30 @ 60°)																																		
Surface Temperature at Application	– Min. 40 °F – Max. 100 °F																																		
Thin With	Clean Water																																		
Clean Up Thinner	Warm Soapy Water																																		
Weight Per Gallon	11.3 lbs.																																		
Storage Temperature	– Min. 40 °F – Max. 90 °F																																		
<p>Tint Bases: Mid-Tone Base (02) Neutral Base (04)</p>	<p>White Tint Base</p>																																		
<p>Technical Assistance: 866-437-5863</p> <p>Spectrum Paint Company, Inc. 15427 E. Skelly Drive Tulsa, OK 741161</p>	<p>Volatile Organic Compounds (VOC)</p> <p>Max VOC < 50 g/L</p>																																		

Dominion Exterior Satin Acrylic SP693

Surface Preparation

All surfaces should be clean, dry, free from dirt, dust, grease, oil, wax and other contaminants. Mold and mildew must be removed. Dull any glossy surfaces. Pressure wash and/or scrape surfaces to remove any cracked, peeling or blistering paint. Do not apply over chalky paint. Spot prime bare areas or surfaces in poor condition with recommended primer.

Caution: Refer to the detergent solution's data and material safety data sheet for instructions on its proper use and handling. For metal surfaces, remove all active rust. Wipe down with paint thinner to remove surface oils.

All new masonry substrates must be allowed to cure for 30 days before priming or painting.

Priming

Wood (Non-bleeding): Apply 1-2 coats of Dominion

Wood (Bleeding): Prime redwood, cedar and other bleeding woods with a stain blocking primer

Galvanized and Aluminum: Apply an acrylic metal primer

Ferrous Metal: Apply a rust-inhibitive metal primer.

Masonry: Apply 1-2 coats of Dominion

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Informational Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

WARRANTY: Spectrum Paint warrants that at the time of sale this product conforms with applicable Spectrum Paint specifications and is free of manufacturing defects. Spectrum Paint's sole liability for products proven defective, and Purchaser's sole remedy, if any, shall be replacement of the product or refund of the purchase price paid, at the sole option of Spectrum Paint. This warranty is not transferable.

TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAW, SPECTRUM PAINT MAKES NO OTHER WARRANTIES, GUARANTEES, OR REPRESENTATIONS OF ANY KIND, EITHER EXPRESS OR IMPLIED, OR BY USAGE OF TRADE, AND HEREBY EXPRESSLY EXCLUDES AND DISCLAIMS ALL IMPLIED WARRANTIES, OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. IN NO EVENT SHALL SPECTRUM BE LIABLE FOR PUNITIVE, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES OF ANY KIND.

Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation may not apply to you. This Limited Warranty gives you specific legal rights and you may have other rights which vary from State to State.

Application

Stir product with a circular, lifting motion before you begin to paint. Dominion may be applied by brush, spray or roller, at a rate of application not to exceed 450 square feet per gallon. Surface texture and porosity will affect actual yield. For best brush application results, use a quality synthetic filament brush. For roller application, use a 3/8" or 1/2" nap cover for smooth surfaces, a 3/4" nap cover for semi-rough surfaces and a 1" or 1 1/2" nap cover for rough surfaces. For spray application, thin with clean water, up to 20% reduction if necessary. Do not apply when surface or air temperatures are below 40 °F. Do not apply to hot surfaces or in direct sunlight. Do not apply if rain is threatening.

Clean Up

Clean up with warm, soapy water followed by a clean water rinse.

USE COMPLETELY OR DISPOSE OF PROPERLY. Dry empty containers may be recycled in a can recycling program. **Local disposal requirements vary; consult your sanitation department or state-designated environmental agency on disposal options.**

Environmental Health & Safety Information

WARNING!

Possible birth defect hazard. Contains, **Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester**, which may cause birth defects based on animal data.

Use only with adequate ventilation. Ensure fresh air entry during application and drying. Avoid contact with eyes and prolonged or repeated contact with skin. Avoid exposure to dust and spray mist by wearing a NIOSH approved respirator during application, sanding and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling.



WARNING: Cancer and Reproductive Harm—
www.P65warnings.ca.gov

FIRST AID: In case of eye contact, flush immediately with plenty of water for at least 15 minutes; for skin, wash thoroughly with soap and water. If symptoms persist, seek medical attention. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

IN CASE OF SPILL – Absorb with inert material and dispose of as specified under "Clean up".

**KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING**

**Refer to Safety Data Sheet for
additional health and safety information.**