



SAFETY DATA SHEET

1

SECTION 1 - Chemical Product and Company Information

Product Name: GUNSTOCK Product Code: 28010

SPECTRUM PAINT
15247 East Skelly Drive
Tulsa, Ok 74116
918-398-2188

24- Hour Emergency (Spill, Leak, Exposure or Accident):
INFOTRAC 800-535-5053
Outside USA, Call Collect 1-352-323-3500

24- Hour Emergency HAZMAT Response and MSDS Help:
EMI 800-510-8510

Product Use: A protective and/or decorative finish or accompanying product (reference label or product data sheet for more information).

Not recommended for: Any other use not detailed on product data sheet or label.

SECTION 2 - Hazards Identification

GHS Ratings:

| | | |
|--------------------|--------------|---|
| Flammable liquid | 3 | Flash point $\geq 23^{\circ}\text{C}$ and $\leq 60^{\circ}\text{C}$ (140°F) |
| Dermal Toxicity | Acute Tox. 4 | Dermal >1000 and ≤ 2000 mg/kg |
| Skin corrosive | 2 | Reversible adverse effects in dermal tissue, Draize score: ≥ 2.3 < 4.0 or persistent inflammation |
| Eye corrosive | 1 | Serious eye damage: Irreversible damage 21 days after exposure, Draize score: Corneal opacity ≥ 3 , Iritis > 1.5 |
| Skin sensitizer | 1 | Skin sensitizer |
| Mutagen | 1B | Known to produce heritable mutations in human germ cells Subcategory 1B, Positive results: In vivo heritable germ cell tests in mammals, Human germ cell tests, In vivo somatic mutagenicity tests, combined with some evidence of germ cell mutagenicity |
| Carcinogen | 1B | Presumed Human Carcinogen, Based on demonstrated animal carcinogenicity |
| Reproductive toxin | 1B | Presumed, Based on experimental animals |
| Aspiration hazard | 1 | Aspiration Toxicity Category 1: Known (regarded)- human evidence - hydrocarbons with kinematic viscosity ≥ 20.5 mm ² /s at 40° C. |

GHS Hazards

| | |
|------|--|
| H226 | Flammable liquid and vapour |
| H304 | May be fatal if swallowed and enters airways |
| H312 | Harmful in contact with skin |
| H315 | Causes skin irritation |
| H317 | May cause an allergic skin reaction |
| H318 | Causes serious eye damage |
| H340 | May cause genetic defects |
| H350 | May cause cancer |
| H360 | May damage fertility or the unborn child |

GHS Precautions

| | |
|------|--|
| P201 | Obtain special instructions before use. |
| P202 | Do not handle until all safety precautions have been read and understood |
| P210 | Keep away from heat/sparks/open flames/hot surfaces – No smoking |
| P233 | Keep container tightly closed |
| P240 | Ground/bond container and receiving equipment |
| P241 | Use explosion-proof electrical/ventilating/light/mixers/equipment |
| P242 | Use only non-sparking tools |
| P243 | Take precautionary measures against static discharge |
| P261 | Avoid breathing dust/fume/gas/mist/vapours/spray |

| | |
|----------------|--|
| P264 | Wash any exposed skin thoroughly after handling |
| P272 | Contaminated work clothing should not be allowed out of the workplace |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection |
| P281 | Use personal protective equipment as required |
| P310 | Immediately call a POISON CENTER or doctor/physician |
| P312 | Call a POISON CENTER or doctor/physician if you feel unwell |
| P321 | Specific treatment (see First Aid section on this label) |
| P322 | Specific measures (see First Aid section on this label) |
| P331 | Do NOT induce vomiting |
| P362 | Take off contaminated clothing and wash before reuse |
| P363 | Wash contaminated clothing before reuse |
| P301+P310 | IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician |
| P302+P352 | IF ON SKIN: Wash with soap and water |
| P303+P361+P353 | IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower |
| P305+P351+P338 | IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing |
| P308+P313 | IF exposed or concerned: Get medical advice/attention |
| P332+P313 | If skin irritation occurs: Get medical advice/attention |
| P333+P313 | If skin irritation or a rash occurs: Get medical advice/attention |
| P370+P378 | In case of fire: Use the NFPA Class B extinguisher for extinction |
| P405 | Store locked up |
| P403+P235 | Store in a well ventilated place. Keep cool |
| P501 | Do not flush to sewer, watershed or waterway. Dispose of product in accordance with applicable local, county, state and federal regulations. |

Signal Word: Danger



SECTION 3 - Composition/Information on Ingredients

| Chemical Name / CAS No. | OSHA Exposure Limits | ACGIH Exposure Limits | Other Exposure Limits |
|-------------------------|----------------------|-----------------------|-----------------------|
|-------------------------|----------------------|-----------------------|-----------------------|

| | | | |
|---|---|---|--|
| Solvent naphtha, petroleum, heavy aromatic 64742-94-5 42% | | | |
| MINERAL SPIRITS 8052-41-3 32% | 500 ppm TWA; 2900 mg/m3 TWA | 100 ppm TWA | NIOSH: 350 mg/m3 TWA 1800 mg/m3 Ceiling (15 min) |
| 2-BUTOXYETHANOL 111-76-2 5% | 50 ppm TWA; 240 mg/m3 TWA | 20 ppm TWA | NIOSH: 5 ppm TWA; 24 mg/m3 TWA |
| Naphthalene 91-20-3 5% | 10 ppm TWA; 50 mg/m3 TWA | 10 ppm TWA | NIOSH: 10 ppm TWA; 50 mg/m3 TWA 15 ppm STEL; 75 mg/m3 STEL |
| Iron oxide (Fe2O3) 1309-37-1 3% | 10 mg/m3 TWA (fume); 15 mg/m3 TWA (total dust, listed under Rouge); 5 mg/m3 TWA (respirable fraction, listed under Rouge) | 5 mg/m3 TWA (respirable particulate matter) | NIOSH: 5 mg/m3 TWA (dust and fume, as Fe) |
| Benzene, 1,2,4-trimethyl- 95-63-6 2% | | | NIOSH: 25 ppm TWA; 125 mg/m3 TWA |
| Silica, amorphous, fumed, crystalline-free 112945-52-5 2% | | | |
| Naphtha, petroleum, hydrotreated heavy 64742-48-9 0.5% | | | |

SECTION 4 - First Aid Measures

Inhalation:

Remove exposed individual to fresh air and assist breathing if necessary. Seek medical attention.

Eye Contact:

Flush eyes with lukewarm water for 15 minutes. Seek medical attention immediately.

Skin:

Remove contaminated clothing, wash area immediately with soap and water. See physician if irritation persists.

Ingestion:

Rinse mouth out immediately. Drink 1 or 2 glasses of water to dilute. DO NOT induce vomiting. Contact physician or poison control center immediately.

SECTION 5 - Fire Fighting Measures

Alcohol Foam, CO2, Dry Chemical

Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. Closed containers may explode when exposed to extreme heat. Do not apply to hot surfaces. Never use welding or cutting torch on or near container (even empty) because product (even residue) may ignite explosively. Liquid and vapor states of this substance are dangerous fire hazards and moderate explosion hazards when exposed to heat or flame.

** Rags, steel wool, and paper towels soaked with this product may spontaneously catch fire if improperly stored and/or discarded. Immediately after each use place rags, steel wool, and paper towels in a sealed water-filled container to prevent spontaneous combustion.

Oxidation may produce carbon and nitrogen oxides.

Clear fire area of unprotected personnel. Do not enter confined space without helmet, face shield, bunker coat, gloves, rubber boots and a positive pressure NIOSH-approved self-contained breathing apparatus. A water stream can scatter flames. A spray of water may be used to cool closed containers to prevent pressure buildup and possible auto ignition or explosion when exposed to extreme heat. If water is used, fog nozzles are preferable. Use the National Fire Protection Association Class B extinguisher.

SECTION 6 - Accidental Release Measures

Stay upwind and away from spill or leak unless wearing appropriate protective equipment. Stop and/or contain discharge if it may be done safely. Keep all sources of ignition away. Ventilate area of spill. Use non-sparking tools for clean up. Cover with inert material to reduce fumes. Keep out of drains, sewer or waterways.

If large spill occurs, alert spill response teams. Contact fire authorities. Notify local health and pollution control agencies.

** Rags, steel wool, and paper towels soaked with this product may spontaneously catch fire if improperly stored and/or discarded. Immediately after each use place rags, steel wool, and paper towels in a sealed water-filled container to prevent spontaneous combustion.

SECTION 7 - Handling and Storage

Handling:

Bond and ground metal containers when transferring liquid. Avoid free fall of liquid in excess of a few inches. Personnel should avoid inhalation of vapors. Personal contact with the product should be avoided. Should contact be made, remove saturated clothing and flush affected skin areas with water. Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in this sheet must be observed.

** Rags, steel wool, and paper towels soaked with this product may spontaneously catch fire if improperly stored and/or discarded. Immediately after each use place rags, steel wool, and paper towels in a sealed water-filled container to prevent spontaneous combustion.

Storage:

Keep product containers cool, dry and away from sources of ignition. Use and store this product with adequate ventilation. DO NOT SMOKE in or near storage areas.

SECTION 8 - Exposure Controls/Personal Protection

| Chemical Name / CAS No. | OSHA Exposure Limits | ACGIH Exposure Limits | Other Exposure Limits |
|---|---|---|---|
| Solvent naphtha, petroleum, heavy aromatic 64742-94-5 | | | |
| MINERAL SPIRITS 8052-41-3 | 500 ppm TWA; 2900 mg/m ³ TWA | 100 ppm TWA | NIOSH: 350 mg/m ³ TWA 1800 mg/m ³ Ceiling (15 min) |
| 2-BUTOXYETHANOL 111-76-2 | 50 ppm TWA; 240 mg/m ³ TWA | 20 ppm TWA | NIOSH: 5 ppm TWA; 24 mg/m ³ TWA |
| Naphthalene 91-20-3 | 10 ppm TWA; 50 mg/m ³ TWA | 10 ppm TWA | NIOSH: 10 ppm TWA; 50 mg/m ³ TWA 15 ppm STEL; 75 mg/m ³ STEL |
| Iron oxide (Fe ₂ O ₃) 1309-37-1 | 10 mg/m ³ TWA (fume); 15 mg/m ³ TWA (total dust, listed under Rouge); 5 mg/m ³ TWA (respirable fraction, listed under Rouge) | 5 mg/m ³ TWA (respirable particulate matter) | NIOSH: 5 mg/m ³ TWA (dust and fume, as Fe) |
| Benzene, 1,2,4-trimethyl- 95-63-6 | | | NIOSH: 25 ppm TWA; 125 mg/m ³ TWA |
| Silica, amorphous, fumed, crystalline-free 112945-52-5 | | | |
| Naphtha, petroleum, hydrotreated heavy 64742-48-9 | | | |

Use local exhaust as required to control vapor concentrations. Avoid prolonged or repeated breathing of vapors.

Respiratory Protection:

If exposure exceeds TLV or PELs, use NIOSH approved respirator to prevent overexposure.

Skin Protection:

Required for prolonged or repeated contact. Wear resistant gloves such as natural rubber, neoprene, buna N or nitrile. An apron should be worn to avoid skin contact.

Eye Protection:

Wear splash proof goggles and face shield if there is a likelihood of contact with eyes.

Hygienic Practices

Wash hands thoroughly before eating or using the restroom. Remove contaminated clothing immediately and do not wear again until it has been properly laundered.

| |
|---|
| SECTION 9 - Physical and Chemical Properties |
|---|

| | |
|--|---|
| <p>Vapor Density Heavier Than Air</p> <p>Boiling range: 150 - 210°C</p> <p>Freezing point: N/A</p> <p>Flammability: N/A</p> <p>Autoignition temperature: 226°C</p> <p>Relative Density: N/A</p> <p>Odor threshold: N/A</p> <p>SPECIFIC GRAVITY 0.8963</p> <p>Partition coefficient (n-octanol/water): N/A</p> <p>Grams VOC less water: N/A</p> <p>% WT. VOLATILE (VOC) 87.8235</p> <p>Lbs VOC/Gallon Solids 87.9227</p> <p>SOLIDS VOL% 7.4553</p> <p>SPREAD @ 1 MIL 119.5837</p> <p>Appearance Colored Liquid</p> <p>Physical State Liquid</p> <p>Coating VOC (g/l) 785.4787</p> <p>Coating VOC (Lb/GI) 6.5549</p> | <p>Evaporation Rate Faster than Butyl Acetate</p> <p>Melting point: N/A</p> <p>Flash point: 108°F, 42°C</p> <p>Explosive Limits: N/A</p> <p>Decomposition temperature: N/A</p> <p>Vapor Pressure N/A</p> <p>pH: N/A</p> <p>Solubility: N/A</p> <p>Viscosity: N/A</p> <p>% VOLUME VOLATILE (VOC) 92.5447</p> <p>% Pig. by wt. 5.3837</p> <p>VOLATILE WT% 87.8235</p> <p>DENSITY (Lb/Gal) 7.4638</p> <p>HAPS (lbs/gI) 0.3513</p> <p>Odor N/A</p> <p>Material VOC (g/l) 785.4787</p> <p>Material VOC (Lb/GI) 6.5549</p> |
|--|---|

| |
|--|
| SECTION 10 - Stability and Reactivity |
|--|

Stability: Stable under normal conditions.

** Rags, steel wool, and paper towels soaked with this product may spontaneously catch fire if improperly stored and/or discarded. Immediately after each use place rags, steel wool, and paper towels in a sealed water-filled container to prevent spontaneous combustion.

Materials to Avoid: Strong oxidizing agents, strong alkalines, strong mineral acids.

Conditions to avoid: high heat, sparks, flames, static discharge.

Hazardous Decomposition: Oxidation may produce carbon and nitrogen oxides.
Hazardous polymerization will not occur.

| |
|---|
| SECTION 11 - Toxicological Information |
|---|

Mixture Toxicity

Dermal Toxicity LD50: 1,745mg/kg

Inhalation Toxicity LC50: 677mg/L

Component Toxicity

| | |
|------------|---|
| 64742-94-5 | Solvent naphtha, petroleum, heavy aromatic Oral LD50: 5,000 mg/kg (Rat) Dermal LD50: 2 mL/kg (Rabbit) Inhalation LC50: 590 mg/m ³ |
| 111-76-2 | 2-BUTOXYETHANOL Oral LD50: 470 mg/kg (Rat) Dermal LD50: 435 mg/kg (Rabbit) Inhalation LC50: 486 ppm |
| 91-20-3 | Naphthalene Oral LD50: 1,110 mg/kg (Rat) Dermal LD50: 1,120 mg/kg (Rabbit) Inhalation LC50: 340 |
| 95-63-6 | Benzene, 1,2,4-trimethyl- Oral LD50: 3,280 mg/kg (Rat) Dermal LD50: 3,160 mg/kg (Rabbit) Inhalation LC50: 18 g/m ³ |
| 64742-48-9 | Naphtha, petroleum, hydrotreated heavy Dermal LD50: 3,160 mg/kg (Rabbit) |

Primary Routes of Entry: Inhalation, Skin Contact, Eyes, Ingestion

Skin:

Skin contact can cause redness, dryness or rash. Prolonged contact can cause irritation, dry skin, cracks, and dermatitis.

Ingestion:

Can cause vomiting, nausea, diarrhea, and gastrointestinal irritation.

Inhalation:

Excessive inhalation of vapors can cause nasal and respiratory irritation, dizziness, weakness, fatigue, nausea, headache possible unconsciousness and even asphyxiation. High vapor concentrations or prolonged breathing of lower concentrations may result in damage to the liver, kidneys, lungs and blood forming organs. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage.

Eyes:

Can cause irritation, redness, tearing and blurred vision.

Carcinogenicity: The following chemicals comprise 0.1% or more of this mixture and are listed and/or classified as carcinogens or potential carcinogens by NTP, IARC, OSHA (mandatory listing), or ACGIH (optional listing).

| <u>CAS Number</u> | <u>Description</u> | <u>% Weight</u> | <u>Carcinogen Rating</u> |
|-------------------|--|-----------------|---|
| 64742-48-9 | Naphtha, petroleum, hydrotreated heavy | 0.5% | Naphtha, petroleum, hydrotreated heavy: EU REACH: Present (P) |
| 8052-41-3 | MINERAL SPIRITS | 32% | MINERAL SPIRITS: EU REACH: Present (P) |
| 91-20-3 | Naphthalene | 5% | Naphthalene: IARC: Possible human carcinogen OSHA: listed |

SECTION 12 - Ecological Information

Ecological Information:

Uncontrolled release of the product may result in contamination of air, ground, waterways and/or sewers.

Component Ecotoxicity

| | |
|--|---|
| Solvent naphtha, petroleum, heavy aromatic | LC50 96 h Pimephales promelas 19 mg/L [static] (IUCLID); LC50 96 h Oncorhynchus mykiss 2.34 mg/L (IUCLID); LC50 96 h Lepomis macrochirus 1740 mg/L [static] (IUCLID); LC50 96 h Pimephales promelas 45 mg/L [flow-through] (IUCLID); LC50 96 h Pimephales promelas 41 mg/L (IUCLID) EC50 48 h Daphnia magna 0.95 mg/L (IUCLID) |
| 2-BUTOXYETHANOL | LC50 96 h Lepomis macrochirus 1490 mg/L [static] (EPA); LC50 96 h Lepomis macrochirus 2950 mg/L (IUCLID) EC50 48 h Daphnia magna >1000 mg/L (EPA) |

| | |
|--|---|
| Naphthalene | LC50 96 h Pimephales promelas 5.74 - 6.44 mg/L [flow-through] (EPA); LC50 96 h Oncorhynchus mykiss 1.6 mg/L [flow-through] (EPA); LC50 96 h Oncorhynchus mykiss 0.91 - 2.82 mg/L [static] (EPA); LC50 96 h Pimephales promelas 1.99 mg/L [static] (IUCLID); LC50 96 h Lepomis macrochirus 31.0265 mg/L [static] (EPA) LC50 48 h Daphnia magna 2.16 mg/L (IUCLID); EC50 48 h Daphnia magna 1.96 mg/L [Flow through] (EPA); EC50 48 h Daphnia magna 1.09 - 3.4 mg/L [Static] (EPA) |
| Iron oxide (Fe2O3) | LC50 96 h Danio rerio 100000 mg/L [static] (approximately, ECHA) |
| Benzene, 1,2,4-trimethyl- | LC50 96 h Pimephales promelas 7.19 - 8.28 mg/L [flow-through] (EPA) EC50 48 h Daphnia magna 6.14 mg/L (IUCLID) |
| Naphtha, petroleum, hydrotreated heavy | LC50 96 h Pimephales promelas 2200 mg/L (IUCLID) |

SECTION 13 - Disposal Considerations

Do not flush to sewer, watershed or waterway. Dispose of product in accordance with applicable local, county, state and federal regulations. See Section 8 for information on exposure control and necessary personal protective equipment.

SECTION 14 - Transportation Information

Ship according to the Department of Transportation (DOT) 49 CFR regulations.

| | | | | |
|--------------------------|-----------------------------|------------------|----------------------|---------------------|
| <u>Agency</u> | <u>Proper Shipping Name</u> | <u>UN Number</u> | <u>Packing Group</u> | <u>Hazard Class</u> |
| DOT | PAINT | UN1263 | III | 3 |
| Freight Class: 55 | | | | |

SECTION 15 - Regulatory Information

SECTION 16 - Disclaimer

Date Prepared: 3/12/2024
Date revised: 2018-10-18 Reviewer Revision 1

THIS DOCUMENT SUPERSEDES ANY PROVISION CONTAINED IN THE FORMS, LETTERS, AND PAPERS OF YOUR COMPANY. THIS PRODUCT IS DESIGNED AND INTENDED FOR PROFESSIONAL APPLICATION ONLY. ALL PRODUCTS SHOULD BE THOROUGHLY TESTED UNDER APPLICATION CONDITIONS PRIOR TO USE. THE INFORMATION CONTAINED HEREIN IS BELIEVED TO BE RELIABLE. HOWEVER, GEMINI MAKES NO WARRANTY CONCERNING THIS PRODUCT, WHETHER EXPRESS OR IMPLIED. INCLUDING THE WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. UNDER NO CIRCUMSTANCES SHALL GEMINI BE LIABLE FOR SPECIAL, INCIDENTAL, CONSEQUENTIAL OR ANY OTHER DAMAGES FROM ALLEGED NEGLIGENCE, BREACH OR WARRANTY, STRICT LIABILITY, OR ANY OTHER LEGAL THEORY, ARISING OUT OF THE USE OR HANDLING OF THIS PRODUCT. THE SOLE REMEDY OF THE BUYER AND THE SOLE LIABILITY OF GEMINI FOR ANY CLAIMS SHALL BE LIMITED TO THE BUYER'S PURCHASE PRICE OF THE PRODUCT WHICH IS THE SUBJECT OF THE CLAIM OR THE AMOUNT ACTUALLY PAID FOR SUCH PRODUCT, WHICHEVER IS LESS. TECHNICAL ADVICE FURNISHED BY GEMINI SHALL NOT CONSTITUTE AN EXPRESS WARRANTY, WHICH IS EXPRESSLY DISCLAIMED. ALL TECHNICAL ADVICE GIVEN IS ACCEPTED AT THE RISK OF THE BUYER.