



# PRODUCT DATA SHEET

## SPEC-PRO® RHINO-GRIP® Multi-Surface Primer/Sealer INT/EXT (SPC69000)

### Product Description

A premium interior/exterior acrylic universal primer formulated to meet the performance requirements of the residential and commercial segments. Especially formulated to block most stains—water, smoke, ink, markers and tannin. Exceptional adhesion to glossy surfaces. Also recommended as a whole house primer for use on properly prepared interior or exterior wood, masonry, plaster, wallboard, cement, brick, stucco, cement composition board, aluminum and wall coverings. Some woods such as redwood and cedar may contain excessive amounts of tannins resulting in stain bleed-through. In such cases, an oil-based primer may be preferable. A second coat may also be used on redwood/cedar. Any tannin bleed should be encapsulated by the first coat and will not bleed into the second.

### Where to Use

Recommended Substrates: Properly repaired aluminum siding, brick, concrete, fiber cement, fiberglass, galvanized metal, gypsum wallboard—drywall, masonry, MDO board, plaster, stucco, vinyl siding and wood. Test on a small area for adhesion to your particular surface before use.

### Product Characteristics

Color	White
Sheen	Low Sheen
Architectural and Industrial Maintenance Category	Primers and Undercoaters
Drying Time	

Temperature	To Touch	To Recoat
75°F / 55% R.H.	1 hour	2 hours

(Cooler temperatures and higher humidity will lengthen drying time)

### Preparation & Priming

**Surface Preparation** Paint only over clean and dry surfaces. Remove all loose paint, oil, grease, dirt, chalk or other contaminants that would hinder the performance of the coating. Mildew must be killed by scrubbing with a solution of a non-soapy detergent such as T.S.P. (Tri-Sodium Phosphate), household bleach and warm water. Thoroughly rinse affected area and let dry prior to painting. Repair all damaged areas, and repair any cracks or splits with appropriate caulk or filler. Glossy surfaces should be sanded. On unfinished porous surfaces such as concrete block, a block filler should be used prior to priming.

### Physical Properties

Mixing	Stir thoroughly, making sure no pigment remains on the bottom of the can.			
Thinning	Thin with water only if necessary up to one pint per gallon			
Surface Temperature	Minimum 50°F, Maximum 110°F - The surface should be dry and the relative humidity should be less than 85%.			
Recommended Thickness	1.5–2.0 mils dry			
Theoretical Coverage	621 ft <sup>2</sup> /gallon at 1 mil dry, assuming no application losses. Coverage will vary depending on color, the surface texture and application technique.			
Coverage Rates per Coat	Dry Mills	Wet Mills	Ft <sup>2</sup> /gal	
	Suggested	1.8	4.7	341
	Minimum	1.5	4.0	400
	Maximum	2.0	5.3	302
Application Equipment	Airless Spray	Pressure	1800–2400 psi	
		Tip	0.015”–0.017”	
	Conventional Spray	Air Pressure	40–70 psi	
		Fluid Pressure	10–20 psi	
	Roller	Use a 3/8” or a 1/2” synthetic roller cover		
	Brush	Use high quality synthetic or nylon bristle brushes.		
Application Considerations	This coating allows for brush, roller, or spray application. Always apply into rather than away from the wet edge, overlapping each pass 50%. Avoid touching up, rolling or brushing back into paint more than ten minutes after applying. Touch up when paint is completely dry. Allow the paint to cure at least ten days.			

**Clean-up & Storage**

Cleanup Use soap and water  
 Storage Temperature Minimum 35°F Maximum 110°F  
 Shelf Life Under Normal Conditions (Unopened) – Two Years

**Safety & Important Information**

Contains ethylene glycol. See SDS for important safety information.

**Use only with adequate ventilation.** Avoid breathing vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer’s directions for respirator use. Avoid contact with eyes. Wash thoroughly after handling. **KEEP OUT OF REACH OF CHILDREN.**

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead). **WARNING!** Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

**Additional Technical Data**

Solids by Volume 38% ± 2  
 AIM Category VOC Limit 2.9 lb/gal (350 g/L)  
 Coating VOC 0.41 lb/gal (49 g/L) – Minus Water and Exempt Materials  
 Material VOC 0.17 lb/gal (20 g/L)  
 Density 10.85 lb/gal (1300 g/L)  
 Packaging 5 Gallon pails and 1 Gallon cans  
 Physical Properties **Flexibility:** Excellent **Weather:** Excellent **Abrasion:** Good  
 Heat Resistance 120-150°F Continuous  
 Safety Information Refer to the Product Data Sheet or Material Safety Data Sheet for safety information.

**Performance Data**

Testing Data

Test Method	ASTM Standard	Result
Freeze/Thaw	ASTM D2243	Pass – 3 Cycles
Heat Stability	ASTM D1849	Pass – 2 Weeks at 120°F

Version: 3/2026

Spectrum Paint Company warrants your satisfaction with the application, appearance, and performance properties of this product when applied to a properly prepared surface in accordance with the label directions. **Spectrum Paint makes no other express warranties. If the product fails to conform to this Limited Warranty, Spectrum Paint will, at your option, furnish replacement product or refund the purchase price. This Limited Warranty excludes (1) labor or costs of labor for the application or removal of any product and (2) all other direct, indirect, incidental, special, or consequential damages.** This Limited Warranty gives you specific legal rights; you may have other rights which vary by state. To make a claim under this Limited Warranty, supply dated proof of purchase to the store of purchase or to Spectrum Paint Company, 15247 E. Skelly Dr., Tulsa, OK 74116.