



# SAFETY DATA SHEET



**85000**

**WHITE WB PRIMER**

3/17/2026

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product Identifier

SPWP-1000

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

A protective and/or decorative finish or accompanying product (reference label or product data sheet for more information). Not recommended for any other use not detailed on product data sheet or label.

### 1.3 Details of the supplier of the safety data sheet

#### Spectrum Paint

15247 E Skelly Dr.

Tulsa, OK 74116

918-398-2188

www.spectrumpaint.com

### 1.4 Emergency telephone number

INFOTRAC

800-535-5053 USA Only

352-323-3500 International (Outside of USA)

## SECTION 2: Hazards Identification

### 2.1 Classification of the substance or mixture

Acute Tox. 2; Carc. 1; STOT RE 1; STOT SE 1

### 2.2 Label elements



Health Hazard

H350-May cause cancer.

H370-Causes damage to organs.

H372-Causes damage to organs through prolonged or repeated exposure.

**85000**

## WHITE WB PRIMER

3/17/2026

---

### Prevention

- P260-Do not breathe dust/fume/gas/mist/vapours/spray.
- P264-Wash skin thoroughly after handling.
- P270-Do not eat, drink or smoke when using this product.
- P271-Use only outdoors or in a well-ventilated area.
- P284-Wear respiratory protection.

### Response

- P304+P340-IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing.
- P308+P311-IF exposed or concerned
- P310-Immediately call a POISON CENTER or doctor/physician.
- P314-Get medical advice/attention if you feel unwell.
- P320-Specific treatment is urgent (see First Aid section on this label).
- P321-Specific treatment (see First Aid section on this label)

### Storage

- P403+P233-Store in a well-ventilated place. Keep container tightly closed.
- P405-Store locked up.

### Disposal

- P501-Dispose of contents and container to a licensed chemical disposal agency in accordance with local, regional and national regulations.

## 2.3 Other hazards

## 2.4 Unknown Acute Toxicity (US)

# SECTION 3: Composition/information on ingredients

## 3.1 Substances

85000

## WHITE WB PRIMER

3/17/2026

## 3.2 Mixtures

Chemical Name	CAS Number	Percentage	Classification
Titanium dioxide	13463-67-7	5% - 10%	Aquatic Chronic 4 Carc. 2 STOT RE 1
Kaolin	1332-58-7	5% - 10%	
Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> )	14807-96-6	5% - 10%	STOT RE 1 STOT SE 1
Water	7732-18-5	15% - 40%	
Nepheline syenite	37244-96-5	10% - 30%	
PROPRIETARY	PROPRIETARY	10% - 30%	
2-Propanol, 1-(1-methyl-2-prop	29911-27-1	1% - 5%	
Silica, amorphous	7631-86-9	0.1% - 1%	Carc. 1A STOT RE 1 STOT SE 3
Propanol, 1(or 2)-(2-methoxyme	34590-94-8	0.1% - 1%	Eye Irrit. 2B Flam. Liq. 4 STOT SE 3
1-Octanol, reaction products w	928768-73-4	0.1% - 1%	
Aluminum oxide (Al <sub>2</sub> O <sub>3</sub> )	1344-28-1	0.1% - 1%	STOT RE 1 STOT SE 3
Silica, amorphous, fumed, crys	112945-52-5	0.1% - 1%	
[[[2-Ethylhexyl]oxy]methyl]oxi	857892-58-1	0.1% - 1%	
Zirconium oxide (ZrO <sub>2</sub> )	1314-23-4	0.1% - 1%	Skin Sens. 1
Chlorite (mineral)	1318-59-8	Less than 0.1%	
Dolomite (CaMg(CO <sub>3</sub> ) <sub>2</sub> )	16389-88-1	Less than 0.1%	
Carbonic acid, magnesium salt	546-93-0	Less than 0.1%	
Polyoxyethylene monoctadecyl	9005-00-9	Less than 0.1%	Skin Irrit. 2 Eye Corr. 1
Cyclohexane	110-82-7	Less than 0.1%	Aquatic Acute 1 Aquatic Chronic 1 Asp. Tox. 1 Skin Irrit. 2 Flam. Liq. 2 STOT SE 2
Phenol, 2,6-bis(1,1-dimethylet	128-37-0	Less than 0.1%	Aquatic Acute 1 Aquatic Chronic 1 Eye Irrit. 2B Repr. 2 STOT RE 2 STOT SE 1
Zinc pyrithione	13463-41-7	Less than 0.1%	Aquatic Acute 1 Aquatic Chronic 1 Skin Irrit. 2 Eye Corr. 1 Repr. 1B Skin Sens. 1 STOT RE 1 STOT SE
Ethanolamine	141-43-5	Less than 0.1%	Acute Tox. 4 Aquatic Acute 2 Aquatic Chronic 3 Skin Corr. 1A Eye Corr. 1 Flam. Liq. 4 Skin Sens. 1 S
Ethyl alcohol	64-17-5	Less than 0.1%	Carc. 1A Eye Irrit. 2A Flam. Liq. 2 Repr. 1A STOT RE 1 STOT SE 3
Phosphoric acid	7664-38-2	Less than 0.1%	Aquatic Acute 3 Skin Corr. 1B Eye Corr. 1 STOT SE 1

**85000**

# WHITE WB PRIMER

3/17/2026

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General notes

#### After inhalation

Remove exposed individual to fresh air and assist breathing if necessary. Vapor or mist can cause headache, nausea and irritation of the nose, throat and lungs in poorly ventilated areas.

#### After skin contact

Irritating to the skin on repeated or prolonged contact. Remove contaminated clothing, wash area immediately with soap and water. See physician if irritation persists.

#### After eye contact

Direct contact may cause eye irritation. Flush eyes with lukewater water for 15 minutes. Seek medical attention immediately.

#### After ingestion

Can cause gastrointestinal irritation. Rinse mouth out immediately. DO NOT induce vomiting. Contact physician or poison control center immediately.

#### Self-protection of the first aider

### 4.2 Most important symptoms and effects, both acute and delayed

### 4.3 Indication of any immediate medical attention and special treatment needed

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Alcohol Foam, CO2, Dry Chemical

#### Unsuitable extinguishing media

### 5.2 Special hazards arising from the substance or mixture

Closed containers exposed to extreme heat may rupture due to pressure buildup. Product will not burn but may spatter if temperature exceeds boiling point of product.

Dried finish can burn, giving off oxides of carbon.

### 5.3 Advice for firefighters

None known. However, fire fighters should wear self-contained breathing apparatus to avoid inhalation if material is involved in a general fire.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

### 6.2 Environmental precautions

### 6.3 Methods and material for containment and cleaning up

Keep out of sewers. Dike spill area and add absorbent earth, sand or sawdust to spilled liquid. Collect absorbent/spilled liquid into metal containers. Dispose of in accordance with local, state and federal regulations. DO NOT incinerate closed containers. Incinerate in approved facilities. Follow all hazard precautions given in this data sheet until container is thoroughly cleaned and destroyed.

### 6.4 Reference to other sections

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Bond and ground metal containers when transferring liquid. Avoid free fall of liquid in excess of a few inches. Personnel should avoid inhalation of vapors. Personal contact with the product should be avoided. Should contact be made, remove saturated clothing and flush affected skin areas with water. Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in this sheet must be observed.

\*\* Keep temperature above 32 Degrees F.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep containers tightly closed when not in use. Keep product containers cool, dry and away from sources of ignition. Use and store this product with adequate ventilation. DO NOT SMOKE in or near storage areas. KEEP FROM FREEZING.

### 7.3 Incompatibilities/Specific end uses(s)

#### Incompatibilities

#### Specific end use(s)

## SECTION 8: Exposure controls/personal protection

85000

WHITE WB PRIMER

3/17/2026

8.1 Control parameters

Cyclohexane(110-82-7)

OSHA PEL	300 ppm
OSHA PEL	1050 mg/m3
ACGIH TLV	100 ppm
NIOSH	300 ppm
NIOSH	1050 mg/m3
QUEBEC	300 ppm
QUEBEC	1030 mg/m3
ONTARIO	100 ppm
BRITISH COLUMBIA	100 ppm

Phenol, 2,6-bis(1,1-dimethylet)(128-37-0)

BRITISH COLUMBIA	2 mg/m3
ONTARIO	2 mg/m3
QUEBEC	2 mg/m3
ACGIH TLV	2 mg/m3
OSHA PEL	10 mg/m3
NIOSH	10 mg/m3

Kaolin(1332-58-7)

NIOSH	10 mg/m3
NIOSH	5 mg/m3
OSHA PEL	5 mg/m3
OSHA PEL	15 mg/m3
ACGIH TLV	2 mg/m3
QUEBEC	2 mg/m3
ONTARIO	2 mg/m3
BRITISH COLUMBIA	2 mg/m3

Aluminum oxide (Al2O3)(1344-28-1)

QUEBEC	5 mg/m3
OSHA PEL	10 mg/m3
OSHA PEL	5 mg/m3

Titanium dioxide(13463-67-7)

OSHA PEL	10 mg/m3
NIOSH	2.4 mg/m3
NIOSH	0.3 mg/m3
ACGIH TLV	0.2 mg/m3
ACGIH TLV	2.5 mg/m3
QUEBEC	10 mg/m3
ONTARIO	10 mg/m3
BRITISH COLUMBIA	3 mg/m3
BRITISH COLUMBIA	10 mg/m3

Ethanolamine(141-43-5)

BRITISH COLUMBIA	3 ppm
QUEBEC	3 ppm
QUEBEC	7.5 mg/m3
ONTARIO	3 ppm
ACGIH TLV	3 ppm
NIOSH	3 ppm
OSHA PEL	3 ppm
OSHA PEL	6 mg/m3
NIOSH	8 mg/m3

Talc (Mg3H2(SiO3)4)(14807-96-6)

NIOSH	2 mg/m3
OSHA PEL	20 mppcf
ACGIH TLV	2 mg/m3

85000

WHITE WB PRIMER

3/17/2026

ONTARIO	2 mg/m3
QUEBEC	2 mg/m3
BRITISH COLUMBIA	2 mg/m3

**Propanol, 1(or 2)-(2-methoxyme(34590-94-8)**

QUEBEC	100 ppm
QUEBEC	606 mg/m3
ONTARIO	100 ppm
ACGIH TLV	50 ppm
OSHA PEL	600 mg/m3
OSHA PEL	100 ppm
NIOSH	100 ppm
NIOSH	600 mg/m3

**Nepheline syenite(37244-96-5)**

ONTARIO	10 mg/m3
---------	----------

**Carbonic acid, magnesium salt(546-93-0)**

QUEBEC	10 mg/m3
BRITISH COLUMBIA	10 mg/m3
BRITISH COLUMBIA	3 mg/m3
NIOSH	10 mg/m3
NIOSH	5 mg/m3

**Ethyl alcohol(64-17-5)**

NIOSH	1900 mg/m3
NIOSH	1000 ppm
OSHA PEL	1000 ppm
OSHA PEL	1900 mg/m3

**Silica, amorphous(7631-86-9)**

OSHA PEL	6 mg/m3
NIOSH	6 mg/m3

**Phosphoric acid(7664-38-2)**

NIOSH	1 mg/m3
OSHA PEL	1 mg/m3
ACGIH TLV	1 mg/m3
BRITISH COLUMBIA	1 mg/m3
ONTARIO	1 mg/m3
QUEBEC	1 mg/m3

**8.2 Engineering Controls/Exposure Controls**

<b>Engineering controls</b>	Avoid prolonged or repeated breathing of vapors.
<b>Environmental exposure controls</b>	Provide general clean air dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below applicable exposure limits.

**8.3 Protective Measures**

<b>Eye/face protection</b>	Wear splash proof goggles and face shield if there is a likelihood of contact with eyes. Provide eyewash station and emergency shower. Use of protective creams, head caps, ets. is recommended.
<b>Hand protection</b>	Polyethylene handling gloves for skin protection. Must be impervious to water and soap.
<b>Other Skin protection</b>	Polyethylene handling gloves for skin protection. Must be impervious to water and soap.
<b>Other protection</b>	
<b>Respiratory protection</b>	
<b>General hygiene consideration</b>	Wash hands thoroughly before eating or using the restroom. Remove contaminated clothing immediately and do not wear again until it has been properly laundered.
<b>Thermal hazards</b>	

**SECTION 9: Physical and chemical properties**

**85000**

**WHITE WB PRIMER**

3/17/2026

**9.1 Information on basic physical and chemical properties**

Autoignition Temp	999 °C	Coating VOC Lbs/Gal	0.65
Coating VOC grams/liter	77.70	Densities	12.7202
Density	12.72	Flash Points	999 °C
Lbs HAPs / Gallon	0.00	Material VOC Lbs/Gal	0.34
Material VOC grams/liter	40.76	Physical State	LIQUID
Solids Vol%	48.06	Specific Gravity	1.5252
State of Matter	Liquid	Upper/lower flammability range	0 - 0 vol %
Weight of VOC	34.02		

**9.2 Other information**

**SECTION 10: Stability and Reactivity**

**10.1 Reactivity**

**10.2 Chemical stability**

Stable under normal conditions.

**10.3 Possibility of hazardous reactions**

**10.4 Conditions to avoid**

Excessive heat, poor ventilation, excessive aging.

**10.5 Incompatible materials**

**10.6 Hazardous decomposition products**

Thermal decomposition or combustion can produce fumes of carbon dioxide and carbon monoxide.

**SECTION 11: Toxicological information**

**11.1 Information on toxicological effects**

**Skin contact**

Skin contact can cause redness, dryness or rash. Prolonged contact can cause irritation, dry skin, cracks, and dermatitis.

**Eye contact**

Can cause irritation, redness, tearing and blurred vision.

**Inhalation**

Vapor harmful. May affect the brain or nervous system causing dizziness, headache or nausea. Breathing high vapor concentrations may produce narcosis. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentration and inhaling the contents may be harmful or fatal.

**Ingestion**

Can cause vomiting, nausea, diarrhea, and gastrointestinal irritation.

**Symptoms related to characteristiccs**

**Acute effects**

**Chronic effects**

**Numerical measures of Toxicity**

**85000****WHITE WB PRIMER**

3/17/2026

**Cyclohexane (110-82-7)**

LC50 Inhalation RAT	> 32880 mg/m <sup>3</sup> no deaths occurred	ECHA
LD50 Ingestion RAT	= 12705 mg/kg	NLM_CIP
LD50 Dermal RABBIT	> 2000 mg/kg no deaths occurred	EU_RAR

**Silica, amorphous, fumed, crys (112945-52-5)**

LD50 Ingestion RAT	= 3160 mg/kg	NLM_CIP
--------------------	--------------	---------

**Phenol, 2,6-bis(1,1-dimethylet (128-37-0)**

LD50 Ingestion RAT	> 2930 mg/kg test substance adminis	EPA_HP
LD50 Dermal RAT	> 2000 mg/kg no deaths occurred	JAPAN_GHS

**Zirconium oxide (ZrO<sub>2</sub>) (1314-23-4)**

LC50 Inhalation RAT	> 4.3 mg/L no deaths occurred	ECHA_API
---------------------	-------------------------------	----------

**Kaolin (1332-58-7)**

LD50 Ingestion RAT	> 5000 mg/kg no deaths occurred	NLM_HSDB
LD50 Dermal RAT	> 5000 mg/kg no deaths occurred	NLM_HSDB

**Aluminum oxide (Al<sub>2</sub>O<sub>3</sub>) (1344-28-1)**

LD50 Ingestion RAT	> 15900 mg/kg no deaths occurred	ECHA
--------------------	----------------------------------	------

**Zinc pyrithione (13463-41-7)**

LD50 Ingestion RAT	= 177 mg/kg	NLM_CIP
LC50 Inhalation RAT	0.05 - 0.5 mg/L	EU_CLH
LD50 Dermal RAT	> 2000 mg/kg	ECHA_API

**Titanium dioxide (13463-67-7)**

LC50 Inhalation RAT	> 5.09 mg/L no deaths occurred	ECHA_API
LD50 Ingestion RAT	> 2000 mg/kg no deaths occurred	ECHA

**Ethanolamine (141-43-5)**

LD50 Ingestion RAT	= 1720 mg/kg	NLM_CIP
LC50 Inhalation RAT	> 1.3 mg/L no deaths occurred	ECHA_API
LD50 Dermal RABBIT	= 1000 mg/kg	JAPAN_GHS

**2-Propanol, 1-(1-methyl-2-prop (29911-27-1)**

LD50 Dermal RABBIT	>= 2000 mg/kg	ECHA_API
LD50 Ingestion RAT	= 1620 µL/kg	NLM_CIP

**Propanol, 1(or 2)-(2-methoxyme (34590-94-8)**

LD50 Ingestion RAT	= 5.35 g/kg	NLM_HSDB
LD50 Dermal RABBIT	= 9500 mg/kg	NLM_CIP

**Ethyl alcohol (64-17-5)**

LD50 Ingestion RAT	= 7060 mg/kg	NLM_CIP
LC50 Inhalation RAT	= 116.9 mg/L males	ECHA_API

**Silica, amorphous (7631-86-9)**

LC50 Inhalation RAT	> 5.01 mg/L no deaths occurred	ECHA
---------------------	--------------------------------	------

85000

WHITE WB PRIMER

3/17/2026

LD50 Ingestion RAT	= 7900 mg/kg in olive oil; no deaths o	ATSDR
LD50 Dermal RABBIT	> 5000 mg/kg no deaths occurred	ECETOC

**Phosphoric acid (7664-38-2)**

LD50 Dermal RABBIT	= 2740 mg/kg	JAPAN_GHS
LD50 Ingestion RAT	= 1530 mg/kg	JAPAN_GHS
LC50 Inhalation RAT	= 3846 mg/m3	OECD_HP

**Water (7732-18-5)**

LD50 Ingestion RAT	> 90 mL/kg	FOOD_JOURN
--------------------	------------	------------

**Polyoxyethylene monoctadecyl (9005-00-9)**

LD50 Ingestion RAT	= 1900 mg/kg	NLM_CIP
--------------------	--------------	---------

**1-Octanol, reaction products w (928768-73-4)**

LC50 Inhalation RAT	= 4.73 mg/m3	ECHA_API
LD50 Dermal RAT	> 2000 mg/kg	ECHA_API

**Skin corrosion/irritation**

**Serious eye damage/eye irritation**

**Respiratory sensitization**

**Skin sensitization**

**Carcinogenicity**

The following chemicals comprise 0.1% or more of this mixture and are listed and/or classified as carcinogens or potential carcinogens by NTP, IARC, OSHA (mandatory listing), or ACGIH (optional listing).

**Germ cell mutagenicity**

**Reproductive toxicity**

**Specific target organ toxicity - single exposure**

**Specific target organ toxicity - repeated exposure**

**Aspiration hazard**

**SECTION 12: Ecological information**

**12.1 Toxicity**

**Ethanolamine (141-43-5)**

EC50	= 65 mg/L (48 h;DAPHNIAMAGNA;(daphnia magna))	IUCLID
------	---	--------

**Propanol, 1(or 2)-(2-methoxyme (34590-94-8)**

LC50	= 1919 mg/L (48 h;DAPHNIAMAGNA;(daphnia magna))	IUCLID
------	---	--------

**Ethyl alcohol (64-17-5)**

LC50	9268 - 1422 (48 h;DAPHNIAMAGNA;(daphnia magna))	IUCLID
EC50	= 2 mg/L (48 h;DAPHNIAMAGNA;(daphnia magna))	EPA

**85000**

# WHITE WB PRIMER

3/17/2026

## 12.2 Persistence and degradability

## 12.3 Bioaccumulative potential

## 12.4 Mobility in soil

## 12.5 Results of PBT and vPvB assessment

## 12.6 Other adverse effects

## 12.7 Additional Information

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Handling for disposal

#### Methods of disposal

Do not flush to sewer, watershed or waterway. Dispose of product in accordance with applicable local, county, state and federal regulations. See Section 8 for information on exposure control and necessary personal protective equipment.

#### Contaminated packaging

## SECTION 14: Transport Information

### 14.1 UN number

### 14.2 UN proper shipping name

WATERBORNE LACQUER NON-HAZARDOUS

### 14.3 Transport hazard class(es)

### 14.4 Packing group

## 14.5 Environmental hazards

## 14.6. Special precautions for user

## 14.7. Transport in bulk according to Annex II of Marpol112 and the IBC Code

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

3

#### SARA313

110-82-7 (Cyclohexane)

1344-28-1 (Aluminum oxide (Al<sub>2</sub>O<sub>3</sub>))

#### Inventory - United States - Section 8(b) Inventory (TSCA)

110-82-7 (Cyclohexane)

128-37-0 (Phenol, 2,6-bis(1,1-dimethylet)

1314-23-4 (Zirconium oxide (ZrO<sub>2</sub>))

1332-58-7 (Kaolin)

1344-28-1 (Aluminum oxide (Al<sub>2</sub>O<sub>3</sub>))

13463-41-7 (Zinc pyrithione)

13463-67-7 (Titanium dioxide)

141-43-5 (Ethanolamine)

14807-96-6 (Talc (Mg<sub>3</sub>H<sub>2</sub>(SiO<sub>3</sub>)<sub>4</sub>))

16389-88-1 (Dolomite (CaMg(CO<sub>3</sub>)<sub>2</sub>))

29911-27-1 (2-Propanol, 1-(1-methyl-2-prop)

34590-94-8 (Propanol, 1(or 2)-(2-methoxyme)

546-93-0 (Carbonic acid, magnesium salt)

64-17-5 (Ethyl alcohol)

7631-86-9 (Silica, amorphous)

7664-38-2 (Phosphoric acid)

7732-18-5 (Water)

9005-00-9 (Polyoxyethylene monooctadecyl)

928768-73-4 (1-Octanol, reaction products w)

85000

# WHITE WB PRIMER

3/17/2026

## VOC

- 110-82-7 (Cyclohexane)
- 141-43-5 (Ethanolamine)
- 34590-94-8 (Propanol, 1(or 2)-(2-methoxyme)
- 64-17-5 (Ethyl alcohol)

## US - California - Proposition 65 - Carcinogens List

- 13463-67-7 (Titanium dioxide)

## Canada - Domestic Substance List (DSL)

- 110-82-7 (Cyclohexane)
- 112945-52-5 (Silica, amorphous, fumed, crys)
- 128-37-0 (Phenol, 2,6-bis(1,1-dimethylet)
- 1314-23-4 (Zirconium oxide (ZrO2))
- 1332-58-7 (Kaolin)
- 1344-28-1 (Aluminum oxide (Al2O3))
- 13463-41-7 (Zinc pyrithione)
- 13463-67-7 (Titanium dioxide)
- 141-43-5 (Ethanolamine)
- 14807-96-6 (Talc (Mg3H2(SiO3)4))
- 29911-27-1 (2-Propanol, 1-(1-methyl-2-prop)
- 34590-94-8 (Propanol, 1(or 2)-(2-methoxyme)
- 37244-96-5 (Nepheline syenite)
- 546-93-0 (Carbonic acid, magnesium salt)
- 64-17-5 (Ethyl alcohol)
- 7631-86-9 (Silica, amorphous)
- 7664-38-2 (Phosphoric acid)
- 7732-18-5 (Water)
- 857892-58-1 ([(2-Ethylhexyl)oxy]methyl]oxi)
- 9005-00-9 (Polyoxyethylene monoocetadecyl)

## Non-Domestic Substances List (NDSL)

- 16389-88-1 (Dolomite (CaMg(CO3)2))

## 15.2 Chemical Safety Assessment


<b>HEALTH</b>	1
<b>FLAMMABILITY</b>	1
<b>PHYSICAL HAZARD</b>	0
<b>PERSONAL PROTECTION</b>	X

1 - Slightly Hazardous

1 - Above 200°F

0-Stable, even under fire conditions and will not re-act with water, etc.

X- Ask Supervisor or Safety Specialist for Handling Instructions



## SECTION 16: Other information

N/A