



SAFETY DATA SHEET



85010

WB SEALER

3/17/2026

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product Identifier

85010

1.2 Relevant identified uses of the substance or mixture and uses advised against

A protective and/or decorative finish or accompanying product (reference label or product data sheet for more information). Not recommended for any other use not detailed on product data sheet or label.

1.3 Details of the supplier of the safety data sheet

Spectrum Paint

15247 E Skelly Dr.
Tulsa, OK 74116
918-398-2188
www.spectrumpaint.com

1.4 Emergency telephone number

INFOTRAC 800-535-5053 USA Only
352-323-3500 International (Outside of USA)

SECTION 2: Hazards Identification

2.1 Classification of the substance or mixture

STOT RE 2

2.2 Label elements



Health Hazard

H373-May cause damage to organs through prolonged or repeated exposure.

Prevention

P260-Do not breathe dust/fume/gas/mist/vapours/spray.

Response

P314-Get medical advice/attention if you feel unwell.

Disposal

P501-Dispose of contents and container to a licensed chemical disposal agency in accordance with local, regional and national regulations.

2.3 Other hazards

2.4 Unknown Acute Toxicity (US)

SECTION 3: Composition/information on ingredients

85010

WB SEALER

3/17/2026

3.1 Substances

3.2 Mixtures

Chemical Name	CAS Number	Percentage	Classification
Water	7732-18-5	60% - 80%	
PROPRIETARY	PROPRIETARY	10% - 30%	
2-Propanol, 1-(2-butoxy-1-meth	29911-28-2	0.5% - 1.5%	STOT RE 2
Diethylene glycol monobutyl et	112-34-5	0.1% - 1%	Eye Irrit. 2A Flam. Liq. 4 STOT RE 1 STOT SE 3
Silica, amorphous, fumed, crys	112945-52-5	0.1% - 1%	
2,4,7,9-Tetramethyl-4,7-decane	17913-76-7	0.1% - 1%	
Octamethylcyclotetrasiloxane	556-67-2	Less than 0.1%	Aquatic Chronic 1 Flam. Liq. 3 Repr. 2

SECTION 4: First aid measures

4.1 Description of first aid measures

General notes

After inhalation

Remove exposed individual to fresh air and assist breathing if necessary. Vapor or mist can cause headache, nausea and irritation of the nose, throat and lungs in poorly ventilated areas.

After skin contact

Irritating to the skin on repeated or prolonged contact. Remove contaminated clothing, wash area immediately with soap and water. See physician if irritation persists.

After eye contact

Direct contact may cause eye irritation. Flush eyes with lukewater water for 15 minutes. Seek medical attention immediately.

After ingestion

Can cause gastrointestinal irritation. Rinse mouth out immediately. DO NOT induce vomiting. Contact physician or poison control center immediately.

Self-protection of the first aider

4.2 Most important symptoms and effects, both acute and delayed

4.3 Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Alcohol Foam, CO2, Dry Chemical

Unsuitable extinguishing media

5.2 Special hazards arising from the substance or mixture

Closed containers exposed to extreme heat may rupture due to pressure buildup. Product will not burn but may spatter if temperature exceeds boiling point of product.

Dried finish can burn, giving off oxides of carbon.

5.3 Advice for firefighters

None known. However, fire fighters should wear self-contained breathing apparatus to avoid inhalation if material is involved in a general fire.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.2 Environmental precautions

6.3 Methods and material for containment and cleaning up

Keep out of sewers. Dike spill area and add absorbent earth, sand or sawdust to spilled liquid. Collect absorbent/spilled liquid into metal containers. Dispose of in accordance with local, state and federal regulations. DO NOT incinerate closed containers. Incinerate in approved facilities. Follow all hazard precautions given in this data sheet until container is thoroughly cleaned and destroyed.

6.4 Reference to other sections

85010

WB SEALER

3/17/2026

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Bond and ground metal containers when transferring liquid. Avoid free fall of liquid in excess of a few inches. Personnel should avoid inhalation of vapors. Personal contact with the product should be avoided. Should contact be made, remove saturated clothing and flush affected skin areas with water. Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in this sheet must be observed.

** Keep temperature above 32 Degrees F.

7.2 Conditions for safe storage, including any incompatibilities

Keep containers tightly closed when not in use. Keep product containers cool, dry and away from sources of ignition. Use and store this product with adequate ventilation. DO NOT SMOKE in or near storage areas. KEEP FROM FREEZING.

7.3 Incompatibilities/Specific end uses(s)

Incompatibilities

Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Diethylene glycol monobutyl et(112-34-5)

ACGIH TLV	10 ppm
QUEBEC	10 ppm
ONTARIO	10 ppm

8.2 Engineering Controls/Exposure Controls

Engineering controls

Avoid prolonged or repeated breathing of vapors.

Environmental exposure controls

Provide general clean air dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below applicable exposure limits.

8.3 Protective Measures

Eye/face protection

Wear splash proof goggles and face shield if there is a likelihood of contact with eyes. Provide eyewash station and emergency shower. Use of protective creams, head caps, ets. is recommended.

Hand protection

Polyethylene handling gloves for skin protection. Must be impervious to water and soap.

Other Skin protection

Polyethylene handling gloves for skin protection. Must be impervious to water and soap.

Other protection

Respiratory protection

General hygiene consideration

Wash hands thoroughly before eating or using the restroom. Remove contaminated clothing immediately and do not wear again until it has been properly laundered.

Thermal hazards

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Autoignition Temp	189 °C	Coating VOC Lbs/Gal	0.78
Coating VOC grams/liter	93.01	Densities	8.6044
Density	8.60	Flash Points	111 °C
Lbs HAPs / Gallon	0.07	Material VOC Lbs/Gal	0.19
Material VOC grams/liter	22.96	Physical State	LIQUID
Solids Vol%	22.21	Specific Gravity	1.0317
State of Matter	Liquid	Upper/lower flammability range	0 - 0 vol %
Weight of VOC	19.16		

9.2 Other information

85010

WB SEALER

3/17/2026

SECTION 10: Stability and Reactivity

10.1 Reactivity

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

10.4 Conditions to avoid

Excessive heat, poor ventilation, excessive aging.

10.5 Incompatible materials

10.6 Hazardous decomposition products

Thermal decomposition or combustion can produce fumes of carbon dioxide and carbon monoxide.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Skin contact

Skin contact can cause redness, dryness or rash. Prolonged contact can cause irritation, dry skin, cracks, and dermatitis.

Eye contact

Can cause irritation, redness, tearing and blurred vision.

Inhalation

Vapor harmful. May affect the brain or nervous system causing dizziness, headache or nausea. Breathing high vapor concentrations may produce narcosis. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentration and inhaling the contents may be harmful or fatal.

Ingestion

Can cause vomiting, nausea, diarrhea, and gastrointestinal irritation.

Symptoms related to characteristiccs

Acute effects

Chronic effects

Numerical measures of Toxicity

Diethylene glycol monobutyl et (112-34-5)

LD50 Dermal RABBIT	= 2700 mg/kg	NLM_CIP
LD50 Ingestion RAT	= 5660 mg/kg	NLM_CIP

Silica, amorphous, fumed, crys (112945-52-5)

LD50 Ingestion RAT	= 3160 mg/kg	NLM_CIP
--------------------	--------------	---------

2-Propanol, 1-(2-butoxy-1-meth (29911-28-2)

LD50 Ingestion RAT	= 1620 µL/kg	NLM_CIP
LC50 Inhalation RAT	> 5.4 mg/L no deaths occurred	ECHA

Octamethylcyclotetrasiloxane (556-67-2)

LC50 Inhalation RAT	= 36 mg/L	ECHA_API
LD50 Dermal RAT	> 2375 mg/kg no deaths occurred	ECHA
LD50 Ingestion RAT	= 1540 mg/kg	NLM_CIP

Water (7732-18-5)

LD50 Ingestion RAT	> 90 mL/kg	FOOD_JOURN
--------------------	------------	------------

85010

WB SEALER

3/17/2026

- Skin corrosion/irritation
- Serious eye damage/eye irritation
- Respiratory sensitization
- Skin sensitization
- Carcinogenicity

The following chemicals comprise 0.1% or more of this mixture and are listed and/or classified as carcinogens or potential carcinogens by NTP, IARC, OSHA (mandatory listing), or ACGIH (optional listing).

- Germ cell mutagenicity
- Reproductive toxicity
- Specific target organ toxicity - single exposure
- Specific target organ toxicity - repeated exposure
- Aspiration hazard

SECTION 12: Ecological information

12.1 Toxicity

Diethylene glycol monobutyl et (112-34-5)

EC50	> 100 mg/L (48 h; DAPHNIAMAGNA; (daphnia magna))	IUCLID
------	--	--------

12.2 Persistence and degradability

12.3 Bioaccumulative potential

12.4 Mobility in soil

12.5 Results of PBT and vPvB assessment

12.6 Other adverse effects

12.7 Additional Information

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Handling for disposal

Methods of disposal

Do not flush to sewer, watershed or waterway. Dispose of product in accordance with applicable local, county, state and federal regulations. See Section 8 for information on exposure control and necessary personal protective equipment.

Contaminated packaging

SECTION 14: Transport Information

14.1 UN number

14.2 UN proper shipping name

WATERBORNE LACQUER NON-HAZARDOUS

14.3 Transport hazard class(es)

14.4 Packing group

14.5 Environmental hazards

14.6. Special precautions for user

14.7. Transport in bulk according to Annex II of Marpol112 and the IBC Code

SECTION 15: Regulatory information

85010

WB SEALER

3/17/2026

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

3

Inventory - United States - Section 8(b) Inventory (TSCA)

- 112-34-5 (Diethylene glycol monobutyl et)
- 29911-28-2 (2-Propanol, 1-(2-butoxy-1-meth)
- 556-67-2 (Octamethylcyclotetrasiloxane)
- 7732-18-5 (Water)

CAA (Clean Air Act) - 1990 Hazardous Air Pollutants

- 112-34-5 (Diethylene glycol monobutyl et)

VHAPS

- 112-34-5 (Diethylene glycol monobutyl et)

VOC

- 112-34-5 (Diethylene glycol monobutyl et)

Canada - Domestic Substance List (DSL)

- 112-34-5 (Diethylene glycol monobutyl et)
- 112945-52-5 (Silica, amorphous, fumed, crys)
- 17913-76-7 (2,4,7,9-Tetramethyl-4,7-decane)
- 29911-28-2 (2-Propanol, 1-(2-butoxy-1-meth)
- 556-67-2 (Octamethylcyclotetrasiloxane)
- 7732-18-5 (Water)

15.2 Chemical Safety Assessment


HEALTH	1
FLAMMABILITY	1
PHYSICAL HAZARD	0
PERSONAL PROTECTION	X

1 - Slightly Hazardous

1 - Above 200°F

0-Stable, even under fire conditions and will not re-act with water, etc.

X- Ask Supervisor or Safety Specialist for Handling Instructions



SECTION 16: Other information

N/A