



SAFETY DATA SHEET



85310

CLEAR WB SATIN

3/17/2026

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product Identifier

85310

1.2 Relevant identified uses of the substance or mixture and uses advised against

A protective and/or decorative finish or accompanying product (reference label or product data sheet for more information). Not recommended for any other use not detailed on product data sheet or label.

1.3 Details of the supplier of the safety data sheet

Spectrum Paint

15247 E Skelly Dr.
Tulsa, OK 74116
918-398-2188
www.spectrumpaint.com

1.4 Emergency telephone number

INFOTRAC 800-535-5053 USA Only
352-323-3500 International (Outside of USA)

SECTION 2: Hazards Identification

2.1 Classification of the substance or mixture

STOT RE 1

2.2 Label elements



Health Hazard

H372-Causes damage to organs through prolonged or repeated exposure.

Prevention

P260-Do not breathe dust/fume/gas/mist/vapours/spray.
P264-Wash skin thoroughly after handling.
P270-Do not eat, drink or smoke when using this product.

Response

P314-Get medical advice/attention if you feel unwell.

Disposal

P501-Dispose of contents and container to a licensed chemical disposal agency in accordance with local, regional and national regulations.

2.3 Other hazards

2.4 Unknown Acute Toxicity (US)

SECTION 3: Composition/information on ingredients**3.1 Substances****3.2 Mixtures**

Chemical Name	CAS Number	Percentage	Classification
Water	7732-18-5	45% - 70%	
PROPRIETARY	PROPRIETARY	10% - 30%	
2-Propanol, 1-(2-butoxy-1-meth	29911-28-2	1% - 5%	STOT RE 2
Diethylene glycol monobutyl et	112-34-5	0.5% - 1.5%	Eye Irrit. 2A Flam. Liq. 4 STOT RE 1 STOT SE 3
Silica, amorphous, precipitate	112926-00-8	0.1% - 1%	Eye Irrit. 2B STOT SE 3
Paraffin waxes and Hydrocarbon	8002-74-2	0.1% - 1%	Eye Irrit. 2B STOT RE 2 STOT SE 3
2,4,7,9-Tetramethyl-4,7-decane	17913-76-7	0.1% - 1%	
Alcohols, C16-18, ethoxylated	68439-49-6	0.1% - 1%	Skin Irrit. 2 Eye Corr. 1
Alcohols, C9-11, ethoxylated	68439-46-3	Less than 0.1%	Aquatic Acute 2 Aquatic Chronic 2 Skin Irrit. 2 Eye Corr. 1
Polyoxyethylene monoocetadecyl	9005-00-9	Less than 0.1%	Skin Irrit. 2 Eye Corr. 1
Octamethylcyclotetrasiloxane	556-67-2	Less than 0.1%	Aquatic Chronic 1 Flam. Liq. 3 Repr. 2
Cyclohexane	110-82-7	Less than 0.1%	Aquatic Acute 1 Aquatic Chronic 1 Asp. Tox. 1 Skin Irrit. 2 Flam. Liq. 2 STOT SE 2
Phenol, 2,6-bis(1,1-dimethylet	128-37-0	Less than 0.1%	Aquatic Acute 1 Aquatic Chronic 1 Eye Irrit. 2B Repr. 2 STOT RE 2 STOT SE 1
Zinc pyrithione	13463-41-7	Less than 0.1%	Aquatic Acute 1 Aquatic Chronic 1 Skin Irrit. 2 Eye Corr. 1 Repr. 1B Skin Sens. 1 STOT RE 1 STOT SE
Ethanolamine	141-43-5	Less than 0.1%	Acute Tox. 4 Aquatic Acute 2 Aquatic Chronic 3 Skin Corr. 1A Eye Corr. 1 Flam. Liq. 4 Skin Sens. 1 S
Ethyl alcohol	64-17-5	Less than 0.1%	Carc. 1A Eye Irrit. 2A Flam. Liq. 2 Repr. 1A STOT RE 1 STOT SE 3
Phosphoric acid	7664-38-2	Less than 0.1%	Aquatic Acute 3 Skin Corr. 1B Eye Corr. 1 STOT SE 1

SECTION 4: First aid measures**4.1 Description of first aid measures****General notes****After inhalation**

Remove exposed individual to fresh air and assist breathing if necessary. Vapor or mist can cause headache, nausea and irritation of the nose, throat and lungs in poorly ventilated areas.

After skin contact

Irritating to the skin on repeated or prolonged contact. Remove contaminated clothing, wash area immediately with soap and water. See physician if irritation persists.

After eye contact

Direct contact may cause eye irritation. Flush eyes with lukewater water for 15 minutes. Seek medical attention immediately.

After ingestion

Can cause gastrointestinal irritation. Rinse mouth out immediately. DO NOT induce vomiting. Contact physician or poison control center immediately.

Self-protection of the first aider**4.2 Most important symptoms and effects, both acute and delayed****4.3 Indication of any immediate medical attention and special treatment needed**

85310-1

CLEAR WB SATIN

3/17/2026

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media Alcohol Foam, CO2, Dry Chemical

Unsuitable extinguishing media

5.2 Special hazards arising from the substance or mixture

Closed containers exposed to extreme heat may rupture due to pressure buildup. Product will not burn but may spatter if temperature exceeds boiling point of product.

Dried finish can burn, giving off oxides of carbon.

5.3 Advice for firefighters

None known. However, fire fighters should wear self-contained breathing apparatus to avoid inhalation if material is involved in a general fire.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.2 Environmental precautions

6.3 Methods and material for containment and cleaning up

Keep out of sewers. Dike spill area and add absorbent earth, sand or sawdust to spilled liquid. Collect absorbent/spilled liquid into metal containers. Dispose of in accordance with local, state and federal regulations. DO NOT incinerate closed containers. Incinerate in approved facilities. Follow all hazard precautions given in this data sheet until container is thoroughly cleaned and destroyed.

6.4 Reference to other sections

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Bond and ground metal containers when transferring liquid. Avoid free fall of liquid in excess of a few inches. Personnel should avoid inhalation of vapors. Personal contact with the product should be avoided. Should contact be made, remove saturated clothing and flush affected skin areas with water. Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in this sheet must be observed.

** Keep temperature above 32 Degrees F.

7.2 Conditions for safe storage, including any incompatibilities

Keep containers tightly closed when not in use. Keep product containers cool, dry and away from sources of ignition. Use and store this product with adequate ventilation. DO NOT SMOKE in or near storage areas. KEEP FROM FREEZING.

7.3 Incompatibilities/Specific end uses(s)

Incompatibilities

Specific end use(s)

SECTION 8: Exposure controls/personal protection

85310-1

CLEAR WB SATIN

3/17/2026

8.1 Control parameters

Cyclohexane(110-82-7)

OSHA PEL	300 ppm
OSHA PEL	1050 mg/m3
NIOSH	300 ppm
NIOSH	1050 mg/m3
QUEBEC	300 ppm
QUEBEC	1030 mg/m3
ACGIH TLV	100 ppm
ONTARIO	100 ppm
BRITISH COLUMBIA	100 ppm

Diethylene glycol monobutyl et(112-34-5)

ONTARIO	10 ppm
ACGIH TLV	10 ppm
QUEBEC	10 ppm

Silica, amorphous, precipitate(112926-00-8)

OSHA PEL	
OSHA PEL	20 mppcf
BRITISH COLUMBIA	4 mg/m3
BRITISH COLUMBIA	1.5 mg/m3

Phenol, 2,6-bis(1,1-dimethylet(128-37-0)

BRITISH COLUMBIA	2 mg/m3
OSHA PEL	10 mg/m3
NIOSH	10 mg/m3
QUEBEC	2 mg/m3
ACGIH TLV	2 mg/m3
ONTARIO	2 mg/m3

Ethanolamine(141-43-5)

ONTARIO	3 ppm
ACGIH TLV	3 ppm
QUEBEC	3 ppm
QUEBEC	7.5 mg/m3
NIOSH	3 ppm
NIOSH	8 mg/m3
OSHA PEL	3 ppm
OSHA PEL	6 mg/m3
BRITISH COLUMBIA	3 ppm

Ethyl alcohol(64-17-5)

OSHA PEL	1000 ppm
OSHA PEL	1900 mg/m3
NIOSH	1900 mg/m3
NIOSH	1000 ppm

Phosphoric acid(7664-38-2)

NIOSH	1 mg/m3
OSHA PEL	1 mg/m3
QUEBEC	1 mg/m3
ACGIH TLV	1 mg/m3
ONTARIO	1 mg/m3
BRITISH COLUMBIA	1 mg/m3

Paraffin waxes and Hydrocarbon(8002-74-2)

BRITISH COLUMBIA	2 mg/m3
ONTARIO	2 mg/m3
ACGIH TLV	2 mg/m3
QUEBEC	2 mg/m3

85310-1

CLEAR WB SATIN

3/17/2026

OSHA PEL	2 mg/m3
NIOSH	2 mg/m3

8.2 Engineering Controls/Exposure Controls

Engineering controls	Avoid prolonged or repeated breathing of vapors.
Environmental exposure controls	Provide general clean air dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below applicable exposure limits.

8.3 Protective Measures

Eye/face protection	Wear splash proof goggles and face shield if there is a likelihood of contact with eyes. Provide eyewash station and emergency shower. Use of protective creams, head caps, ets. is recommended.
Hand protection	Polyethylene handling gloves for skin protection. Must be impervious to water and soap.
Other Skin protection	Polyethylene handling gloves for skin protection. Must be impervious to water and soap.
Other protection	
Respiratory protection	
General hygiene consideration	Wash hands thoroughly before eating or using the restroom. Remove contaminated clothing immediately and do not wear again until it has been properly laundered.

Thermal hazards

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Autoignition Temp	189 °C	Coating VOC Lbs/Gal	0.88
Coating VOC grams/liter	105.08	Densities	8.6202
Density	8.62	Flash Points	105 °C
Lbs HAPs / Gallon	0.11	Material VOC Lbs/Gal	0.28
Material VOC grams/liter	34.12	Physical State	LIQUID
Solids Vol%	28.79	Specific Gravity	1.0336
State of Matter	Liquid	Upper/lower flammability range	0 - 0 vol %
Weight of VOC	28.46		

9.2 Other information

SECTION 10: Stability and Reactivity

10.1 Reactivity

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

10.4 Conditions to avoid

Excessive heat, poor ventilation, excessive aging.

10.5 Incompatible materials

10.6 Hazardous decomposition products

Thermal decomposition or combustion can produce fumes of carbon dioxide and carbon monoxide.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

85310-1

CLEAR WB SATIN

3/17/2026

Skin contact

Skin contact can cause redness, dryness or rash. Prolonged contact can cause irritation, dry skin, cracks, and dermatitis.

Eye contact

Can cause irritation, redness, tearing and blurred vision.

Inhalation

Vapor harmful. May affect the brain or nervous system causing dizziness, headache or nausea. Breathing high vapor concentrations may produce narcosis. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentration and inhaling the contents may be harmful or fatal.

Ingestion

Can cause vomiting, nausea, diarrhea, and gastrointestinal irritation.

Symptoms related to characteristiccs

Acute effects

Chronic effects

Numerical measures of Toxicity

85310-1

CLEAR WB SATIN

3/17/2026

Cyclohexane (110-82-7)

LD50 Dermal RABBIT	> 2000 mg/kg no deaths occurred	EU_RAR
LD50 Ingestion RAT	= 12705 mg/kg	NLM_CIP
LC50 Inhalation RAT	> 32880 mg/m3 no deaths occurred	ECHA

Diethylene glycol monobutyl et (112-34-5)

LD50 Ingestion RAT	= 5660 mg/kg	NLM_CIP
LD50 Dermal RABBIT	= 2700 mg/kg	NLM_CIP

Silica, amorphous, precipitate (112926-00-8)

LD50 Ingestion RAT	> 20000 mg/kg no deaths occurred	ECHA
--------------------	----------------------------------	------

Phenol, 2,6-bis(1,1-dimethylet (128-37-0)

LD50 Ingestion RAT	> 2930 mg/kg test substance adminis	EPA_HP V
LD50 Dermal RAT	> 2000 mg/kg no deaths occurred	JAPAN_GHS

Zinc pyrithione (13463-41-7)

LD50 Dermal RAT	> 2000 mg/kg	ECHA_API
LD50 Ingestion RAT	= 177 mg/kg	NLM_CIP
LC50 Inhalation RAT	0.05 - 0.5 mg/L	EU_CLH

Ethanolamine (141-43-5)

LC50 Inhalation RAT	> 1.3 mg/L no deaths occurred	ECHA_API
LD50 Ingestion RAT	= 1720 mg/kg	NLM_CIP
LD50 Dermal RABBIT	= 1000 mg/kg	JAPAN_GHS

2-Propanol, 1-(2-butoxy-1-meth (29911-28-2)

LD50 Ingestion RAT	= 1620 µL/kg	NLM_CIP
LC50 Inhalation RAT	> 5.4 mg/L no deaths occurred	ECHA

Octamethylcyclotetrasiloxane (556-67-2)

LC50 Inhalation RAT	= 36 mg/L	ECHA_API
LD50 Ingestion RAT	= 1540 mg/kg	NLM_CIP
LD50 Dermal RAT	> 2375 mg/kg no deaths occurred	ECHA

Ethyl alcohol (64-17-5)

LD50 Ingestion RAT	= 7060 mg/kg	NLM_CIP
LC50 Inhalation RAT	= 116.9 mg/L males	ECHA_API

Alcohols, C9-11, ethoxylated (68439-46-3)

LD50 Ingestion RAT	= 1400 mg/kg	NZ_CCID
--------------------	--------------	---------

Alcohols, C16-18, ethoxylated (68439-49-6)

LD50 Ingestion RAT	= 1260 mg/kg	NLM_CIP
LD50 Dermal RABBIT	2000 - 5000 mg/kg	AICIS

Phosphoric acid (7664-38-2)

LD50 Dermal RABBIT	= 2740 mg/kg	JAPAN_GHS
LD50 Ingestion RAT	= 1530 mg/kg	JAPAN_GHS
LC50 Inhalation RAT	= 3846 mg/m3	OECD_HP V

85310-1

CLEAR WB SATIN

3/17/2026

Water (7732-18-5)		
LD50 Ingestion RAT	> 90 mL/kg	FOOD_JOURN
Paraffin waxes and Hydrocarbon (8002-74-2)		
LD50 Ingestion RAT	> 5000 mg/kg in arachis oil; no death	CHEMVIEW
LD50 Dermal RABBIT	> 3600 mg/kg	NLM_CIP
Polyoxyethylene mono-octadecyl (9005-00-9)		
LD50 Ingestion RAT	= 1900 mg/kg	NLM_CIP

Skin corrosion/irritation

Serious eye damage/eye irritation

Respiratory sensitization

Skin sensitization

Carcinogenicity

The following chemicals comprise 0.1% or more of this mixture and are listed and/or classified as carcinogens or potential carcinogens by NTP, IARC, OSHA (mandatory listing), or ACGIH (optional listing).

Germ cell mutagenicity

Reproductive toxicity

Specific target organ toxicity - single exposure

Specific target organ toxicity - repeated exposure

Aspiration hazard

SECTION 12: Ecological information

12.1 Toxicity

Diethylene glycol monobutyl et (112-34-5)		
EC50	> 100 mg/L (48 h; DAPHNIAMAGNA;(daphnia magna))	IUCLID
Ethanolamine (141-43-5)		
EC50	= 65 mg/L (48 h; DAPHNIAMAGNA;(daphnia magna))	IUCLID
Ethyl alcohol (64-17-5)		
LC50	9268 - 1422 (48 h; DAPHNIAMAGNA;(daphnia magna))	IUCLID
EC50	= 2 mg/L (48 h; DAPHNIAMAGNA;(daphnia magna))	EPA

12.2 Persistence and degradability

12.3 Bioaccumulative potential

12.4 Mobility in soil

12.5 Results of PBT and vPvB assessment

12.6 Other adverse effects

12.7 Additional Information

85310-1

CLEAR WB SATIN

3/17/2026

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Handling for disposal

Methods of disposal

Do not flush to sewer, watershed or waterway. Dispose of product in accordance with applicable local, county, state and federal regulations. See Section 8 for information on exposure control and necessary personal protective equipment.

Contaminated packaging

SECTION 14: Transport Information

14.1 UN number

14.2 UN proper shipping name

WATERBORNE LACQUER NON-HAZARDOUS

14.3 Transport hazard class(es)

14.4 Packing group

14.5 Environmental hazards

14.6. Special precautions for user

14.7. Transport in bulk according to Annex II of Marpol112 and the IBC Code

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

3

SARA313

110-82-7 (Cyclohexane)

Inventory - United States - Section 8(b) Inventory (TSCA)

- 110-82-7 (Cyclohexane)
- 112-34-5 (Diethylene glycol monobutyl et)
- 128-37-0 (Phenol, 2,6-bis(1,1-dimethylet)
- 13463-41-7 (Zinc pyrithione)
- 141-43-5 (Ethanolamine)
- 29911-28-2 (2-Propanol, 1-(2-butoxy-1-meth)
- 556-67-2 (Octamethylcyclotetrasiloxane)
- 64-17-5 (Ethyl alcohol)
- 68439-46-3 (Alcohols, C9-11, ethoxylated)
- 68439-49-6 (Alcohols, C16-18, ethoxylated)
- 7664-38-2 (Phosphoric acid)
- 7732-18-5 (Water)
- 8002-74-2 (Paraffin waxes and Hydrocarbon)
- 9005-00-9 (Polyoxyethylene monoctadecyl)

CAA (Clean Air Act) - 1990 Hazardous Air Pollutants

112-34-5 (Diethylene glycol monobutyl et)

VHAPS

112-34-5 (Diethylene glycol monobutyl et)

VOC

- 110-82-7 (Cyclohexane)
- 112-34-5 (Diethylene glycol monobutyl et)
- 141-43-5 (Ethanolamine)
- 64-17-5 (Ethyl alcohol)

Canada - Domestic Substance List (DSL)

- 110-82-7 (Cyclohexane)
- 112-34-5 (Diethylene glycol monobutyl et)
- 112926-00-8 (Silica, amorphous, precipitate)
- 128-37-0 (Phenol, 2,6-bis(1,1-dimethylet)
- 13463-41-7 (Zinc pyrithione)
- 141-43-5 (Ethanolamine)

85310-1


CLEAR WB SATIN

3/17/2026

17913-76-7 (2,4,7,9-Tetramethyl-4,7-decane)
29911-28-2 (2-Propanol, 1-(2-butoxy-1-meth)
556-67-2 (Octamethylcyclotetrasiloxane)
64-17-5 (Ethyl alcohol)
68439-46-3 (Alcohols, C9-11, ethoxylated)
68439-49-6 (Alcohols, C16-18, ethoxylated)
7664-38-2 (Phosphoric acid)
7732-18-5 (Water)
8002-74-2 (Paraffin waxes and Hydrocarbon)
9005-00-9 (Polyoxyethylene monooctadecyl)

15.2 Chemical Safety Assessment

HEALTH	1	1 - Slightly Hazardous
FLAMMABILITY	1	1 - Above 200°F
PHYSICAL HAZARD	0	0-Stable, even under fire conditions and will not re-act with water, etc.
PERSONAL PROTECTION	X	X- Ask Supervisor or Safety Specialist for Handling Instructions



SECTION 16: Other information

N/A