



Paint & Primer In One Exterior Satin Finish

DESCRIPTION

A durable 100% acrylic latex satin house paint with a Lifetime warranty when applied according to all label directions on a properly prepared surface



FORMULA ANALYSIS

Resin Type – 100% Acrylic
Sheen/Type Finish: 10-20 @60° / Satin
Weight per Gallon = 10.36 lbs. /gal % ± .2
Percent Solids by Weight = 50.55 % ± 2%
Percent Solids by Volume = 40.70 % ± 2%
Viscosity Range = 95-105 KU
V.O.C. = Less than 50 gm/L 0.042lbs/gal
Coverage = 300-400 sq. ft. per gallon.
MPI# 15

PRODUCT FEATURES

- High Hiding Formula
- Exceptional Durability
- Superior Fade Resistance
- Stain & Mildew Resistant
- Superior Chalking Resistance
- Excellent application with brush, roller or spray
- Adheres difficult substrates including aged alkyds

Color and Bases Available

White	D Deep Base
P Pastel Base	N Neutral Base
T Tint Base	

RECOMMENDED USE:

Exterior new, weathered or previously painted surfaces such as masonry, stucco, concrete block, brick and concrete. May also be used on properly prepared wood, factory primed siding and cement board.

THINNING: Thin sparingly with water if necessary for spray application use .013 - .017 spray tip.

DRY TIME: Dries in 3 hours, recoat in 16-24 hours. High humidity or low temperature may increase dry time. After 2-4 weeks, cured paint may be cleaned with a mild, non-abrasive liquid detergent. Dry Paint film is mildew resistant.

COVERAGE: 300-400 sq. ft. per gallon depending on the porosity of the surface to be painted.

CLEAN UP: Wash tools with warm water and soap immediately after applying.

Properly dispose of all soiled rags. To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only)

STORAGE: Protect unused product from freezing.

APPLICATION METHODS:

This paint can be used over latex or oil based paint. Intermix all containers for color uniformity. Stir thoroughly before and during use. Certain colors may require more than one coat. Do not apply over a surface that has not been properly prepared. Do not apply if rain or dew is expected within 24 hrs or if outside temperature could drop below 35°. Do not apply in hot sun; follow shade around house. Do not over spread. Use a premium brush or pad applicator. If spray applied back brushing is recommended to assure adequate penetration into the substrate. For best performance; apply two coats on new surfaces after priming. Allow new masonry to cure at least 30 days before coating.



Paint & Primer In One Exterior Semi-Gloss Finish

DESCRIPTION

A durable 100% acrylic latex semi-gloss house paint with a Lifetime warranty when applied according to all label directions on a properly prepared surface

FORMULA ANALYSIS

Resin Type – 100% Acrylic
Sheen/Type Finish: 45-55 @60° / Semi-Gloss
Weight per Gallon = 10.10 lbs. /gal % ± .2
Percent Solids by Weight = 45.40 % ± 2%
Percent Solids by Volume = 36.00% ± 2%
Viscosity Range = 95-105 KU
V.O.C. = Less than 50 gm/L 0.04 lbs./gal
Coverage = 400-500 sq. ft. per gallon.
MPI# 11

RECOMMENDED USE:

Exterior new, weathered or previously painted surfaces such as masonry, stucco, concrete block, brick and concrete. May also be used on properly prepared wood, factory primed siding and cement board.

THINNING: Thin sparingly with water if necessary for spray application use .013 - .017 spray tip.

DRY TIME: Dries to touch in 3 hours, recoat in 16-24 hours. High humidity or low temperature may increase dry time. After 2-4 weeks, cured paint may be cleaned with a mild, non-abrasive liquid detergent. Dry Paint film is mildew resistant.

COVERAGE: 400-500. sq. ft. per gallon depending on the porosity of the surface to be painted.

CLEAN UP: Wash tools with warm water and soap immediately after applying.

Properly dispose of all soiled rags. To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only)

STORAGE: Protect unused product from freezing.

APPLICATION METHODS:

This paint can be used over latex or oil based paint. Intermix all containers for color uniformity. Stir thoroughly before and during use. Certain colors may require more than one coat. Do not apply over a surface that has not been properly prepared. Do not apply if rain or dew is expected within 24 hrs or if outside temperature could drop below 35°. Do not apply in hot sun; follow shade around house. Do not over spread. Use a premium brush or pad applicator. If spray applied back brushing is recommended to assure adequate penetration into the substrate. For best performance; apply two coats on new surfaces after priming. Allow new masonry to cure at least 30 days before coating



PRODUCT FEATURES

- High Hiding Formula
- Exceptional Durability
- Superior Fade Resistance
- Stain & Mildew Resistant
- Superior Chalking Resistance
- Excellent application with brush, roller or spray
- Exceptional brushing
- Adheres difficult substrates including aged alkyls

Color and Bases Available

White	D Deep Base
P Pastel Base	N Neutral Base
T Tint Base	