



Spec-Pro® Buildermax® Alkyd Enamel Interior Satin (26300)

Spec-Pro® Buildermax® Alkyd Satin is a premium enamel that features excellent hardness, toughness and block resistance. This highly durable lustrous finish is wear and burnish resistant, protects against moisture and is washable. Recommended for interior trim and wall surfaces.

Recommended Substrates: Drywall, Wood, Concrete, Plaster, Masonry, Steel, Galvanized Metal & Aluminum

Application: Mix thoroughly before use. May be applied by brush, roller or airless spray. Do not thin. Do not add linseed or other oils. For airless spray, use a .015" - .019" tip at 2000 psi, adjust pressure as needed. Do not apply when the surface or air temperature is below 40°F (4°C). Provide good ventilation and warmth for normal drying. Apply at 450-500 sq ft/gal (11-12 m²/L). Actual coverage may vary depending on surface texture, porosity and application method. For best hiding, tint primers toward finish coat color. Certain shades of yellow, orange, pink and red may require multiple coats. Important: Alkyd and oil-based enamels may yellow in time in the absence of light, especially sunlight.

Product Type: Alkyd Resin
Volume Solids: 54% ± 1%
Weight Solids: 73% ± 1%
Sheen: 10 - 35 units @ 85°
VOC: <380 g/L (3.17 lbs./gal.)
Dry Film Thickness: 1.7-1.9 mils
Wet Film Thickness: 3.2-3.6 mils
Flash Point: 105°F (41°C)

Dry Time at 77°F at 50% relative humidity: to touch = 4 hours; recoat = overnight; Low temperature, high humidity, thick films or poor ventilation will increase these times.

Theoretical Coverage @ 1 mil dry: 861 sq ft/gal (21 m²/L)

Practical Coverage: Apply at 450-500 sq ft/gal (11-12 m²/L). Actual coverage may vary depending on substrate & application method.

Clean Up Solvent: Mineral Spirits. Clean up tools immediately with mineral spirits. Clean spills right away with damp cloth. Washing Instructions: After 30 days or when paint has fully cured, areas may be washed using a non-abrasive, mild detergent solution and cellulose sponge.

General Surface Preparation: All surfaces must be sound, dry, clean and free of oil, grease, dirt, rust, mildew, form release agents, curing compounds, loose and flaking paint and other foreign substances. **WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear an NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Prep & Primer Depends on Substrate. Contact Your Local Spectrum Rep for Recommendations.

Precautions: DANGER! COMBUSTIBLE LIQUID AND VAPOR. HARMFUL OR FATAL IF SWALLOWED. ASPIRATION HAZARD-CAN ENTER LUNGS AND CAUSE DAMAGE. HARMFUL IF INHALED. MAY CAUSE CENTRAL NERVOUS SYSTEM EFFECTS, INCLUDING DIZZINESS, HEADACHE OR NAUSEA. CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION. OVEREXPOSURE MAY CAUSE LIVER, KIDNEY DAMAGE. CONTAINS CRYSTALLINE SILICA WHICH CAN CAUSE LUNG CANCER AND OTHER LUNG DAMAGE IF INHALED. WHEN TINTED, CONTAINS ETHYLENE GLYCOL WHICH CAN CAUSE SEVERE KIDNEY DAMAGE WHEN INGESTED AND HAS BEEN SHOWN TO CAUSE BIRTH DEFECTS IN LABORATORY ANIMALS. USE ONLY WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN. NOTICE: Products in this series contain solvents. Prior to use, read and follow product specific MSDS and label information. First Aid: for skin contact, wash thoroughly with soap and water. If any product remains, gently rub with petroleum jelly, vegetable or mineral/baby oil then wash again with soap and water. Repeat as needed. Remove contaminated clothing. For eye contact, flush immediately with plenty of water for at least 15 minutes. Get medical attention. If swallowed, get medical attention immediately. If inhalation causes discomfort, remove to fresh air. **KEEP FROM FREEZING.**