

# Paint & Primer In One Interior Matte Finish

### **DESCRIPTION**

Apremium interior acrylic paint that is designed to meet the highest expectations of the most demanding consumer. This low odor, zero VOC, environmentally friendly product is Asthma & Allergy and Master Painter Institute certified

#### **FORMULA ANALYSIS**

Resin Type – 100% Acrylic Sheen/Type Finish: 0-5 @60° / Flat Weight per Gallon = 11.65 lbs ± .2 /gal Percent Solids by Weight = 65.57 % ± 2% Percent Solids by volume = 42.2 % ± 2% Viscosity Range = 90-100 KU V.O.C. = Less than 5 g/L Coverage = 250-400 sq. ft. per gallon. MPI Certification - # 53



#### **PRODUCT FEATURES**

- High Hiding Formula
- Exceptional Durability
- Superior Fade Resistance
- Stain & Mildew Resistant
- Scrubbable
- Low Odor
- Zero VOC

### **Colors & Tinting**

White
Pastel Base
Tint Base
Deep Base
Neutral Base

## **RECOMMENDED USE:**

Previously painted or properly prepared and primed interior surfaces. This product is Asthma & Allergy and Master Painter Institute certified.

**THINNING:** Thin sparingly with water if necessary for spray application use .015 - .019 spray tip.

**DRY TIME:** Dries to the touch in 1-2 hours at 77° and 50% humidity. Recoat if necessary after 4 hours. High humidity or low temperature may increase dry time. After 2-4 weeks, cured paint may be cleaned with a mild, non-abrasive liquid detergent. Darker colors may require additional dry time between coats. Dry Paint film is mildew resistant.

**COVERAGE:** 250-400 sq.ft. per gallon depending on the porosity of the surface to be painted.

**CLEAN UP:** Wash tools with warm water and soap immediately after applying.

Properly dispose of all soiled rags. To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only)

**STORAGE:** Protect unused product from freezing.

# **APPLICATION METHODS:**

- Do not apply over a surface that has not been thoroughly prepared.
- Stir thoroughly before and during use. Intermix all containers for color uniformity.
- Use a premium nylon/polyester brush, 3/8" nap roller cover or pad applicator.
- Do not over spread.
- For best performance; apply two coats on new surfaces after priming.