

# Paint & Primer In One Interior Semi-Gloss Finish

#### **DESCRIPTION**

A premium interior acrylic paint that is designed to meet the highest expectations of the most demanding consumer. This low odor, zero VOC, environmentally friendly product is Master Painter Institute certified

#### **FORMULA ANALYSIS**

Resin Type - 100% Acrylic

Sheen/Type Finish: 35-45 @60° / Semi-Gloss

Weight per Gallon = 10.05 lbs /gal  $\% \pm 2\%$ Percent Solids by Weight = 47.87  $\% \pm 2\%$ Percent Solids by volume = 33.34  $\% \pm 2\%$ 

Viscosity Range = 90-100 KU

V.O.C. = Less than 5 gm/L 0.04 lbs/gal Coverage = 250-400 sq. ft. per gallon.

MPI Certification - # 54



### **PRODUCT FEATURES**

- High Hiding Formula
- Exceptional Durability
- Superior Fade Resistance
- Stain & Mildew Resistant
- Scrubbable
- Low Odor
- Zero VOC

## Colors & Tinting

White

Pastel Base

Tint Base

Deep Base

**Neutral Base** 

## **RECOMMENDED USE:**

Previously painted or properly prepared and primed interior surfaces. This product is Master Painter Institute certified.

**THINNING:** Thin sparingly with water if necessary for spray application use .013 - .017 spray tip.

**DRY TIME:** Dries to the touch in 1-2 hours at 77° and 50% humidity. Recoat if necessary after 4 hours. High humidity or low temperature may increase dry time. After 2-4 weeks, cured paint may be cleaned with a mild, non-abrasive liquid detergent. Darker colors may require additional dry time between coats. Dry Paint film is mildew resistant.

**COVERAGE:** 250-400 sq. ft. per gallon depending on the porosity of the surface to be painted.

**CLEAN UP:** Wash tools with warm water and soap immediately after applying.

Properly dispose of all soiled rags. To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only)

**STORAGE:** Protect unused product from freezing.

## **APPLICATION METHODS:**

- Do not apply over a surface that has not been thoroughly prepared.
- Stir thoroughly before and during use. Intermix all containers for color uniformity.
- Use a premium nylon/polyester brush, 3/8" nap roller cover or pad applicator.
- Do not over spread.
- For best performance; apply two coats on new surfaces after priming.