



SPEC-PRO®
4000
Series

Spec-Pro 4000 Primer

Spec-Pro 4000 Primer: a durable, quality interior vinyl acrylic sealer/primer. Seals the surface to create an even, sound surface for the topcoat to be applied. Recommended for use on properly prepared new or previously painted wallboard and wood.

Recommended Substrates: Gypsum Wallboard-Drywall, Oriented Strand Board, Particle Board, Wood

Application: Stir product thoroughly before using and regularly when in use. When using more than one container of the same color, intermix to ensure color uniformity. Apply with a high quality brush, roller, paint pad, or by airless spray equipment. Where necessary, apply a second coat. **Airless Spray:** Pressure 2000 psi, tip 0.015" - 0.021". Use a polyester/nylon brush and 3/8" - 3/4" nap roller cover. Thinning is not usually required, but if necessary, thin with up to 1/4 pint of water per U.S. gallon of paint. Permissible temperature during application is 50 to 90 degrees Fahrenheit. Covers approximately 400sq. ft./gal on smooth, nonporous surfaces.

Product Type: Vinyl Acrylic
Volume Solids: 25.0 ± 2.0%
Weight Solids: 39 ± 2.0%
Weight Per Gallon: 10.5 lbs. ± 2 lbs.
Flash Point: 200°F. or greater
Sheen: Flat
Wet Film Thickness: 4.0 mils
Dry Film Thickness: 1.0 mils
VOC: <50 g/L (.83 lbs/gal)

Dry Time: to touch = 30 mins; recoat = 4 hours; Dry time @ 77 degrees Fahrenheit at 50% relative humidity

Thinner: Clean water.

Clean Up: Warm, soapy water.

Disposal: Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Do not pour down a drain or storm sewer.

Surfaces to be coated must be dry, clean, sound and free from all contamination including loose and peeling paint, dirt, grease, oil, wax, concrete curing agents and bond breakers, chalk, efflorescence, mildew, rust, product fines and dust. Remove loose paint, chalk and efflorescence by wire brushing, scraping, sanding and/or pressure washing. Putty all nail holes and caulk all cracks and open seams. Sand all glossy, rough and patched surfaces. Feather back all rough edges to sound surface by sanding. Apply primer over soluble stains before coating to avoid bleeding. Prime all bare and porous substrates with an appropriate primer. Mortar should cure for at least 30 days and preferably 90 days prior to priming. Fill block with an appropriate block filler. Surfaces previously coated with water thinned cement-based paint must be prepared with extra care. If the material appears to be adhering lightly, a masonry sealer may be applied to seal the surface. Check adhesion by applying a piece of masking tape. If the sealer peels off and has loose particles, remove all chalking or crumbling material, re-seal and re-check adhesion. Nails or screws should be countersunk, and they along with any indentations should be mudded flush with the surface, sanded smooth and cleaned to remove any dust, then prime prior to painting the substrate. Plaster, hardcoat, skim coat, or other alkaline surfaces should be allowed to cure for at least 30 days prior to priming with an alkali resistant primer. Unpainted wood or wood in poor condition should be sanded smooth, wiped clean, then primed. Any knots or resinous areas must be primed before painting.

Warning: Overexposure may cause kidney damage. Contains Crystalline Silica. Use only with adequate ventilation. Avoid breathing dust, vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes. Wash thoroughly after handling.

First Aid: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. If swallowed, do not induce vomiting. Call physician immediately. **WARNING:** This product contains chemicals known to the state of California to cause cancer, birth defects or other reproductive harm. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Obtain and read the MSDS prior to using this product.