



RHINO-GRIP™

RHINO-GRIP™ 8000 Interior/Exterior Universal Primer/Sealer (68000)

A premium interior exterior acrylic universal primer formulated to meet the performance requirements of the residential and commercial segments. Especially formulated to block most stains-water, smoke, ink, markers and tannin. Exceptional adhesion to glossy surfaces. Also recommended as a whole house primer for use on properly prepared interior or exterior wood, masonry, plaster, wallboard, cement, brick, stucco, cement composition board, aluminum and wall coverings.

Recommended Substrates: Aluminum Siding, Brick, Concrete, Fiber Cement, Fiberglass, Gypsum Wallboard-Drywall, Masonry, MDO Board, Plaster, Stucco, Vinyl Siding and Wood.

Application: Stir thoroughly before using and occasionally when in use. When using more than one can of the same color, intermix to ensure color uniformity. **USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN.** Read all label and Safety Data Sheets (SDS) information prior to use. Apply with a high quality brush, roller, paint pad, or by spray equipment, Severe stains may require two coats of primer. Brushing is the preferred method of application over chalky substrates. If painting will be interrupted for more than 15 minutes, keep brushes wet by wrapping them in tinfoil or plastic wrap. Airless spray pressure 2000 psi; tip 0.015" - 0.021". Spray equipment must be handled with due care and in accordance with manufacturer's recommendation. High-pressure injection of coatings into the skin by airless equipment may cause serious injury. Use a Polyester/Nylon brush; 3/8"-3/4" nap roller cover; Do Not Thin.

Product Type: 100% Acrylic Latex
Volume Solids: 40% +/- 2%
Weight Solids: 52% +/- 2%
Sheen: Low Sheen
VOC: <50 g/L (0.4 lbs/gal.)
Dry Film Thickness: 1.6 mils
Wet Film Thickness: 4.0 mils
Flash Point: Over 200°F (93°C)

Dry Time at 77°F at 50% relative humidity: to touch = 30 minutes; recoat = 1 hour; to full cure = 30 days; drying times listed may vary depending on temperature, humidity, film build, color, and air movement.

Coverage: Approximately 400 sq ft/gal per U.S. gallon on smooth, nonporous surfaces.

Clean Up: Clean tools with warm, soapy water.

Disposal: Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.

General Surface Preparation: Surface must be clean and dry. Remove dirt, mildew, grease and other surface contamination. Remove loose paint, excessive amounts of chalk, and efflorescence by wire brushing, scraping, sanding, and/or pressure washing. Repair all moisture problems. Blistering and peeling issues are commonly caused by moisture behind the paint film. Putty all nail holes, and caulk all cracks and open seams. Sand all rough, and patched surfaces. Sanding is not required if the surface is properly and thoroughly cleaned. **WARNING!** If you scrape, sand, or remove old paint, you may release lead dust or fumes. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Precautions: **WARNING! HARMFUL IF INHALED. HARMFUL IF SWALLOWED. CAUSES RESPIRATORY TRACT IRRITATION.** Do not breathe vapor or mist. Do not swallow. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling. Provide fresh air ventilation during and after application and drying. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Use personal protective equipment as required. These warnings encompass the product series. Prior to use, read and follow product-specific SDS and label information. **FIRST AID:** If swallowed, rinse mouth with water (only if the person is conscious). Call physician immediately. Do not induce vomiting unless directed to do so by medical personnel. If in eyes, rinse with water for 15 minutes. Check for and remove any contact lenses. If on skin, rinse well with water. Wash with soap and water. Get medical attention if irritation develops. If inhaled, remove to fresh air. Keep out of reach of children. **EMERGENCY SPILL INFORMATION:** (412) 434-4515.